This is an electronic reprint of the original article.
This reprint may differ from the original in pagination and typographic detail.

Canik, J. M.; Briesemeister, A.R.; McLean, A.G.; Groth, M.; Leonard, A.W.; Lore, J. D.; Moser, A. L.

Testing the role of molecular physics in dissipative divertor operations through helium plasmas at DIII-D

Published in:
Physics of Plasmas

DOI:
[10.1063/1.4982057](https://doi.org/10.1063/1.4982057)

Published: 01/05/2017

Document Version
Publisher's PDF, also known as Version of record

Please cite the original version:

Canik, J. M., Briesemeister, A. R., McLean, A. G., Groth, M., Leonard, A. W., Lore, J. D., & Moser, A. L. (2017). Testing the role of molecular physics in dissipative divertor operations through helium plasmas at DIII-D. *Physics of Plasmas*, 24(5), [056116]. <https://doi.org/10.1063/1.4982057>

This material is protected by copyright and other intellectual property rights, and duplication or sale of all or part of any of the repository collections is not permitted, except that material may be duplicated by you for your research use or educational purposes in electronic or print form. You must obtain permission for any other use. Electronic or print copies may not be offered, whether for sale or otherwise to anyone who is not an authorised user.

Testing the role of molecular physics in dissipative divertor operations through helium plasmas at DIII-D

J. M. Canik, A. R. Briesemeister, A. G. McLean, M. Groth, A. W. Leonard, J. D. Lore, A. Moser, and BPMIC Team

Citation: [Physics of Plasmas](#) **24**, 056116 (2017); doi: 10.1063/1.4982057

View online: <https://doi.org/10.1063/1.4982057>

View Table of Contents: <http://aip.scitation.org/toc/php/24/5>

Published by the [American Institute of Physics](#)

Articles you may be interested in

[Attainment of a stable, fully detached plasma state in innovative divertor configurations](#)

[Physics of Plasmas](#) **24**, 056112 (2017); 10.1063/1.4979193

[Confinement improvement in the high poloidal beta regime on DIII-D and application to steady-state H-mode on EAST](#)

[Physics of Plasmas](#) **24**, 056114 (2017); 10.1063/1.4982058

[Key results from the first plasma operation phase and outlook for future performance in Wendelstein 7-X](#)

[Physics of Plasmas](#) **24**, 055503 (2017); 10.1063/1.4983629

[Divertor plasma detachment](#)

[Physics of Plasmas](#) **23**, 055602 (2016); 10.1063/1.4948273

[Compatibility of lithium plasma-facing surfaces with high edge temperatures in the Lithium Tokamak Experiment](#)

[Physics of Plasmas](#) **24**, 056110 (2017); 10.1063/1.4977916

[Multi-field/-scale interactions of turbulence with neoclassical tearing mode magnetic islands in the DIII-D tokamak](#)

[Physics of Plasmas](#) **24**, 056106 (2017); 10.1063/1.4977533

PHYSICS TODAY

WHITEPAPERS

MANAGER'S GUIDE

Accelerate R&D with
Multiphysics Simulation

READ NOW

PRESENTED BY

COMSOL

Testing the role of molecular physics in dissipative divertor operations through helium plasmas at DIII-D

J. M. Canik,^{1,a)} A. R. Briesemeister,¹ A. G. McLean,² M. Groth,³ A. W. Leonard,⁴ J. D. Lore,¹ A. Moser,⁴ and BPMIC Team

¹Oak Ridge National Laboratory, Oak Ridge, Tennessee 37830, USA

²Lawrence Livermore National Laboratory, Livermore, California 94551, USA

³Aalto University, Espoo 02150, Finland

⁴General Atomics, San Diego, California 92186, USA

(Received 2 December 2016; accepted 27 February 2017; published online 10 May 2017)

Recent experiments in DIII-D helium plasmas are examined to resolve the role of atomic and molecular physics in major discrepancies between experiment and modeling of dissipative divertor operation. Helium operation removes the complicated molecular processes of deuterium plasmas that are a prime candidate for the inability of standard fluid models to reproduce dissipative divertor operation, primarily the consistent under-prediction of radiated power. Modeling of these experiments shows that the full divertor radiation can be accounted for, but only if measures are taken to ensure that the model reproduces the measured divertor density. Relying on upstream measurements instead results in a lower divertor density and radiation than is measured, indicating a need for improved modeling of the connection between the divertor and the upstream scrape-off layer. These results show that fluid models are able to quantitatively describe the divertor-region plasma, including radiative losses, and indicate that efforts to improve the fidelity of the molecular deuterium models are likely to help resolve the discrepancy in radiation for deuterium plasmas. *Published by AIP Publishing.*

[<http://dx.doi.org/10.1063/1.4982057>]

I. INTRODUCTION

It is generally expected that in future fusion devices, including ITER, a significant fraction of the input power will need to be exhausted via volumetric processes (i.e., radiation) within the scrape-off layer (SOL) and divertor.¹ This is needed, since otherwise the projections of the SOL heat flux width indicate unmitigated heat flux far in excess of the power handling capabilities of present and anticipated plasma-facing component technologies.^{2,3} The standard approach to mitigating the heat flux is by establishing a strongly radiating divertor scenario:⁴ by dispersing power through radiation, the heat flux is spread over a much larger area than just that directly wetted by the divertor plasma.

The achievement of a highly radiating, dissipative divertor has been demonstrated numerous times in experiments,^{5,6} and the basic processes involved have been known for many years.⁵ Likewise, numerical models of the SOL and divertor have been able to produce a similarly dissipative state.⁷ Indeed, these models have been used to predict the operating scenario for the ITER divertor, where again heat flux reduction via radiation is expected to be required.⁸ However, it has recently emerged that when directly compared to experimental measurements for the purpose of code validation, standard 2D fluid models of the edge plasma have failed to reproduce the magnitude of the SOL and divertor radiated power.⁹ This is problematic given that these same codes are used to project and optimize divertor scenarios as part of the

design of next-step devices, for which accurately simulating the radiative dissipation is central.

The code-experiment mismatch takes the form of a consistent under-prediction of the divertor radiated power by the codes by a factor of approximately 2, termed “radiation shortfall.” This has been observed initially in carbon-walled machines, in particular DIII-D and JET. One obvious possibility is simply that the carbon erosion model used within the codes is inaccurate, which might be expected given the complex chemical processes which dominate at low plasma temperature for carbon.¹⁰ Indeed, modeling efforts often simply treated the chemical sputtering yields of carbon as a free parameter, adjusted specifically to reproduce the measured radiated power.¹¹ However, more recent analyses indicate that this approach results in visible carbon emission in the models that is significantly higher than is measured (i.e., that too much carbon is included in the model).¹² Further, the radiation deficit is also observed in modeling of the JET ITER-Like Wall, which consists entirely of metals with no carbon used as a plasma facing component (PFC).¹³

This may implicate deuterium as the culprit behind the radiation discrepancy, possibly indicating insufficient atomic or molecular physics rates. This is a likely possibility especially for molecular deuterium reactions, where many pathways are possible and implementing a comprehensive model that encompasses all including the associated radiative losses is challenging. Significant effort is being put into improving molecular deuterium modeling within the plasma models,¹⁴ with some success in improving various comparisons to experiment.¹² However, the SOL and divertor is a strongly coupled system, with complex interdependencies such that

Note: Paper JI3 2, Bull. Am. Phys. Soc. **61**, 170 (2016).

^{a)}Invited speaker.

inadequacies in many parts of the physics basis could contribute to the radiation deficit. Hence, the underlying source of radiation shortfall may be something other than the deuterium atomic and molecular physics completeness and accuracy, and improving on these will not fully resolve the discrepancy if the true issue is a more fundamental inadequacy of the 2D fluid plasma model in describing SOL and divertor physics. Indeed, it is well-known that this model neglects or incompletely treats many important physics features that are thought to be important elements in describing the boundary plasma (e.g., kinetic effects and turbulence).

In the present work, we describe a set of experiments and modeling activities aimed at testing the possibility whether the atomic and molecular physics basis is indeed the likely underlying inadequacy responsible for the observed radiation deficit. These made use of helium plasmas designed to test radiative divertor operation. Operating in helium has the advantage of simply removing the complicated molecular processes under suspicion from the scenario, indirectly allowing their contribution to radiation shortfall to be assessed. Helium operation also removes chemical sputtering of carbon, largely eliminating carbon radiation at low divertor temperatures where physical sputtering yields are also small. Hence, the simple presence or absence of a radiation deficit in helium plasmas should offer insight into the possible sources of error in the model. The analysis described here also explores the possible role of transport physics and how the measured density is matched in modeling and attempts to isolate these effects from atomic physics on radiation levels. Overall, this work aims to inform the likelihood that whether better capturing the complicated molecular physics in deuterium will improve the overall agreement with experiment.

II. SETUP OF EXPERIMENTS AND CORRESPONDING MODELING

The radiated power density P_{rad} can be written as

$$P_{\text{rad}} = n_e n_Z L_Z(T_e, n_e \tau),$$

where n_e and n_Z are the electron and impurity densities, respectively, L_Z is the radiation power function which is determined by atomic physics and the charge state distribution of the plasma which in turns depends on the electron temperature T_e and the impurity transport through the replacement time τ . Already, this illustrates the range of possible sources of error in the calculation of radiation, as it depends on the background plasma (n_e , T_e), impurity generation and transport physics (n_Z, τ), and atomic physics (L_Z). Studies of radiative divertor operation in helium plasmas have been performed due to the potential to simplify the set of physical processes involved and hence perform a more fundamental test of models' ability to capture radiation physics. Since helium plasmas do not involve molecular processes, the set of atomic reactions that could contribute to L_Z are limited and are able to be treated more completely. The atomic physics rates may themselves not be necessarily more accurate than those for deuterium, but they can be included more comprehensively. Furthermore, the lack of chemical

erosion removes carbon as a strong radiator at low divertor temperatures, so that the source and density of the radiator are less uncertain. By testing the ability of the models to capture radiation in this simplified environment, we can evaluate whether improving the atomic and molecular physics included in modeling deuterium plasmas is likely to resolve the radiation discrepancy, or whether it is caused by other physics missing from the models.

The experiments were performed on the DIII-D tokamak.¹⁵ The general plasma characteristics are similar to experiments described elsewhere that have been optimized for divertor diagnosis.¹⁶ The neutral beams used to heat the discharges were converted to helium operation, so that strong heating could be performed while maintaining high purity of the helium plasma. The injected beam power in the discharges studied here was 2 MW, for a total power (including Ohmic heating) of ~ 3 – 3.2 MW. The plasmas described here remained in the L-mode throughout the time periods of interest. The outer strike point position was varied on a shot-by-shot basis (i.e., shots were repeated at varying strike point locations) in order to build a 2D map of electron density (n_e) and temperature (T_e) measurements using the Divertor Thomson Scattering (DTS) system.¹⁶ The density was ramped during each shot, as illustrated in the time traces shown in Figure 1; the shot numbers in consideration are 166819–826. The range of density sweep spanned the divertor regimes of interest, from strongly attached at low density up to strongly detached with high radiated power at high density. Data are combined from different discharges to produce the 2D n_e and T_e maps. Data with line-averaged density within 5% of that at the center of the time window were included. The strike point position was only varied over

FIG. 1. Time traces of (a) line-averaged electron density, (b) plasma current, and divertor electron (c) density and (d) temperature near the outer strike point. Time slices of interest indicated by vertical lines.

a limited range such that the outer divertor volume was probed; data from the inner divertor leg are not available from these discharges using the DTS system. The other primary diagnostics used in this work include upstream density and temperature measurements using Thomson scattering and charge exchange recombination spectroscopy and measurements of the 2D radiated power distribution from tomographic inversions of bolometric measurements.

Modeling of these experiments has been performed using the SOLPS (Scrape-Off Layer Plasma Simulation) suite of codes.¹⁷ This uses a 2D fluid model for the plasma transport via the B2.5 code, which is coupled to a Monte Carlo calculation of the kinetic neutral transport using the EIRENE code¹⁸ (in the present work, the 1999 version of EIRENE is used). Plasma transport is assumed to be classical in the direction parallel to magnetic field lines, with kinetic corrections implanted by flux limiters on the electron and ion heat flux, as well as the parallel viscosity. Transport across magnetic flux surfaces is governed by user-specified cross-field transport coefficients D , χ_e , and χ_i . The plasma sheath at the intersection between plasma and material surfaces is implemented via boundary conditions on the fluid equations, with standard values for the sheath heat transmission coefficients and sonic parallel flow $v_{||}$ ($M = v_{||}/c_s = 1$, where c_s is the sound speed) assumed. Physical and chemical sputtering of the PFCs by ion impact is included via standard databases, and atomic reactions for ionization, recombination, and charge exchange are included using rates as in Ref. 19. It should be noted that $E \times B$ and diamagnetic drifts are not included in the present work due to associated numerical difficulties. This makes the present effort unlikely to capture the in-out divertor asymmetries that have been previously measured and modeled, as these are known to be impacted by drifts.²⁰ However, the impact of drifts on the radiation levels has been previously shown to be modest ($\sim 10\%$),⁹ and further drifts are expected to be less important at the low divertor temperatures of most interest for dissipative divertor analysis.²¹ In any case, the present work focusses on the outer divertor due to both the available measurements and this limitation in the modeling.

In principle, the cross-field transport coefficients representing anomalous diffusion should be taken from a physics-based transport model in order for the overall edge plasma model to be truly predictive. However, as reliable SOL transport models are lacking (although they are currently an active area of research), experimental measurements are instead used to constrain the SOLPS modeling. This is accomplished by adjusting the transport coefficients using an iterative procedure²² until a good match to the measured n_e and T_e upstream profiles is produced. While in principle the same method can be used to reproduce the T_i profile, in practice ion measurements in the SOL are typically sparse and difficult to interpret when available; instead, a typical value for the ion heat diffusivity ($1 \text{ m}^2/\text{s}$) is used. This procedure effectively allows the upstream electron profiles to be set as input into the SOLPS modeling; while a fairly standard method for analysis of experiments using edge transport codes, this has important implications which will be discussed below.

III. COMPARISON OF RADIATION CHARACTERISTICS WITH MATCHED UPSTREAM PROFILES

Three time slices from the helium discharges have been modeled using the above method, as indicated by the vertical lines in Figure 1. These times span from an attached divertor with high temperature ($T_e^{\text{div}} \sim 15 \text{ eV}$) and modest radiation to a highly radiating, low-temperature ($T_e^{\text{div}} \sim 2 \text{ eV}$) high density ($n_e^{\text{div}} \sim 3 \times 10^{20} \text{ m}^{-3}$) case. 2D profiles of the divertor radiation are shown in Figure 2, based on bolometric inversions. At the lowest density, the radiation in the outer divertor is localized near the surface of the PFC, and as the density is increased, the radiation zone moves upwards towards the X-point. However, at the highest density considered, the radiation is still dominantly from within the divertor region. This is noteworthy, as previous helium detachment experiments have shown that radiation often collapses to the X-point, leading to little power flowing into the SOL and divertor itself;¹⁹ this scenario is less interesting from the standpoint of studying a dissipative divertor. In the present experiments, the power flowing into the SOL remains high and is dissipated within the divertor volume; this combined with the achievement of a high-recycling SOL regime (evidenced by the high divertor densities) makes the present study more relevant to testing the ability of models to reproduce dissipative divertor physics. Times later in the discharges show strong X-point radiation and are hence excluded from the present analysis. While not shown here,

FIG. 2. Measured radiated power density in divertor at time slices of interest during density ramp.

carbon is effectively removed from the two high density time slices (due to a lack of chemical sputtering), with very little visible carbon emission measured compared either to the earlier time point (where physical sputtering is higher) or to similar deuterium plasmas.

The upstream profiles resulting from the fitting technique described above are shown in Figure 3 for the lowest-density time slice ($t = 1600$ ms). As can be seen, the profiles are well-reproduced by SOLPS (the quality of the fit is similar for the other two time points). In all calculations, the experimental power into the SOL (~ 3 MW) is set as a boundary condition, but the power flux to the target is not directly constrained in the modeling. The SOLPS-calculated radiated power distributions are shown in Figure 4 and show good qualitative agreement with measurements: the radiation is localized near the target at low density and moves towards but not all the way to the X-point at the highest density modeled. However, the magnitude of the total radiation integrated over the outer divertor is consistently lower from SOLPS modeling than the measured value as shown in Figure 5, which shows the radiation from experiment and from modeling as a function of the upstream separatrix density. This is similar to the case in deuterium as described above, although the discrepancy is lower in magnitude (with SOLPS being only $\sim 25\%$ – 35% lower than experiment at high densities, in comparison to a factor of ~ 2 reported for deuterium). Thus, while the radiation deficit is reduced in helium, for matched upstream plasma profiles a substantial radiation shortfall remains.

A possible source of this radiation deficit has been identified from comparisons of the divertor profiles between modeling and experiment. With the upstream profiles used as a constraint on the modeling, the reproduction of the divertor plasma characteristics is not guaranteed. Fortunately, DIII-D has the unique capability of directly measuring n_e and T_e within the divertor volume based on Thomson scattering as

FIG. 3. Measured (blue triangles) and modeled (black curves) upstream electron (a) temperature and (b) density.

FIG. 4. Modeled radiated power density in divertor at time slices of interest during density ramp.

described above. The measured and modeled density distributions for the lowest-density time slices are shown in Figure 6 and show a consistently lower density in the SOLPS modeling than is measured by DTS. The full 2D profiles in the outer divertor are shown (panels a and b), as well as a 1-D profile of the same data plotted along a flux tube very near the separatrix. The discrepancy is evident from the 2D measurements which show much more spatially extended high-density regions than the modeling. The degree of the discrepancy can be quantified by averaging the density over the outer divertor volume (i.e., the region highlighted in panels a and b) and shows a density that is consistently $\sim 40\%$ less in the modeling than experiment across the three times analyzed (Table I).

FIG. 5. Total power radiated in outer divertor from experiment and modeling, as a function of upstream separatrix density.

FIG. 6. 2D profiles of (a) modeled and (b) measured electron density, and poloidal profiles along a near-separatrix flux tube for low density time slice. In panel (c), electron density versus poloidal connection length; $L_{\text{pol}} = 0$ indicates the outer target, and the X-point is located near $L_{\text{pol}} \sim 0.2$ m.

TABLE I. Average outer divertor density measured and modeled either matching the upstream or the divertor.

Time (ms)	$\langle n_{\text{div}} \rangle^{\text{EXPT}}$ (10^{19} m^{-3})	$\langle n_{\text{div}} \rangle^{\text{SOLPS}}$ Match upstream (10^{19} m^{-3})	$\langle n_{\text{div}} \rangle^{\text{SOLPS}}$ Match divertor (10^{19} m^{-3})
1600	3.9	2.7	3.5
2400	8.0	4.5	7.9
2800	11.3	6.9	11.2

Given this discrepancy, the persistence of the radiation deficit is not surprising as the radiated power is highly dependent on the electron density.

IV. COMPARISON OF RADIATION CHARACTERISTICS WITH MATCHED DIVERTOR DENSITY

A second set of modeling has been performed focusing on matching the divertor density and temperature between modeling and experiment in order to test the role of parallel transport physics in contributing to the radiation deficit. This was accomplished by increasing the upstream electron density self-similarly while keeping the T_e profile fixed, which has the effect of raising the divertor density, until the divertor-averaged electron density in the modeling agreed with the DTS measurement (Table I). This required upstream densities $\sim 50\%$ higher than measured. The resulting divertor n_e and T_e parallel profiles are shown in Figure 7. As can be

seen, good agreement between the measured and modeled profiles is produced across the entire distance between the X-point and target surface, for both the density and the temperature. While the average divertor density is constrained to agree with measurements, the poloidal density gradient is not and so the degree of agreement in the gradient is noteworthy, as is the agreement in the electron temperature profile in the divertor, which is entirely unconstrained. Finally, as illustrated in Figure 8, while only a scalar quantity (the divertor-averaged n_e) is used to constrain the divertor parameters, good agreement is obtained in the full 2D distributions of n_e and T_e .

These cases with the divertor density and temperature matched allow a more direct comparison of the radiated power for the purposes of evaluating the atomic physics involved. As shown in Figure 9, the total radiation in the outer divertor for these cases agrees very well with experiment for the highly radiating, high density cases, with modeling being within roughly 10% of the measured values. The degree of agreement is imperfect, in that the 2D distribution does not fully match experiment: as can be seen in Figure 10, the radiation pattern on the inner divertor leg is quite different between code and experiment (c.f. Figure 2(c)) and is likely attributable to the neglect of drifts which would tend to lower T_e on the inner leg²⁰ and hence strongly affect radiation. This confirms the focus here on the outer divertor, where measurements are available to ensure that

FIG. 7. Poloidal profiles of electron (a)–(c) temperature and (d)–(f) density for low (a) and (d), medium (b) and (e), and high (c), (f) density time slices for modeling cases with average divertor density matched to experiment.

FIG. 8. 2D profiles of electron (a) and (b) temperature and (c) and (d) density from (a) and (c) modeling and (b) and (d) measurement for the medium-density time slice with modeled average divertor density matched to experiment.

the density and temperature profiles are well-reproduced in the modeling.

The result that helium modeling with a good match to the divertor density does not show an appreciable radiation shortfall confirms that 2D fluid models like SOLPS are in principle capable of quantitatively capturing the divertor radiation levels measured in experiment for the simpler case with helium as the main ion species. These results are also consistent with the efforts ongoing to improve the deuterium molecular physics set incorporated in the modeling, in that removing these uncertainties by running in helium also removed the large radiation discrepancy. However, these results also show that the larger challenge, at least in the helium experiments being analyzed, is achieving the experimental density and temperature throughout the divertor volume in the modeling, especially when only the upstream profiles are available from measurements.

FIG. 9. Total power radiated in the outer divertor from experiment (blue circles) and modeling (red squares) as a function of divertor-averaged density.

FIG. 10. 2D profiles of radiated power density from modeling of high density time slice with divertor density matched.

V. IMPLICATIONS OF UPSTREAM MISMATCH

Although as described above the divertor density and temperature profiles from SOLPS agree very well with DTS measurements, the upstream profiles are no longer constrained to match measurement. This connection between the divertor and the main SOL is an outstanding issue and an open research area that will be necessary to understand in order to predict the divertor characteristics for given upstream parameters. Towards this end, it is instructive to inspect the degree of mismatch and explore possible sources of error, whether in the transport model itself, or through boundary conditions or other input to the model. Two major pieces of the overall SOLPS transport model are considered: the parallel electron heat transport model and parallel pressure or momentum balance. Each of these is central to the overall parallel collisional transport model that is employed in SOLPS.

As described above, SOLPS uses a fluid model for parallel electron heat transport, using classical collisional closures for the heat flux (also with kinetic corrections via flux limiters, although these are not important for the high collisionalities studied here). The electron component of the overall parallel heat transport is important since the classical conductivity is much higher for electrons than ions, by the square root of the electron/ion mass ratio.²³ Figure 11 shows that the upstream electron temperature profile agrees very well with experimental measurement. Further, as described above, the poloidal temperature profile within the divertor region also agrees very well with measurements. This implies that, provided the power loss terms are accurately modeled (which is the case for these helium experiments, which show good agreement in the radiated power between code and experiment), the SOLPS model is sufficient to quantitatively describe the electron heat transport over the entire region from the main SOL near the midplane of the tokamak, all the way through the divertor to the PFC surface.

Of larger concern is the discrepancy in the measured electron density in the upstream SOL and that used in the modeling, with that latter being $\sim 50\%$ higher than experiment for all time slices considered for the cases with matched divertor density. This implies a potential issue with the parallel pressure balance, since the overly high electron

FIG. 11. Measured (blue triangles) and modeled (black curves) upstream electron (a) temperature and (b) density for the medium density case with average divertor density matched.

density is effectively adding extra pressure to the upstream SOL. Pressure balance is a foundational concept in SOL physics, where the momentum and continuity equations can be combined to show that the total pressure should be constant along field lines, unless a strong momentum loss is present²³

$$\frac{\partial}{\partial l} (p_e + p_i + n_i m_i V_i^2) = S_{mom} = m_i n_i v_i n_0 \langle \sigma v \rangle_{CX} + S_{\perp}.$$

Momentum loss is expected due to collisions with neutrals and is expected to be strong at low electron temperature (<10 eV).²⁴ Hence, one expects that within the divertor, where the neutral density is high and temperature low, pressure loss should be strong; otherwise, pressure can be expected to be constant along the magnetic field.

In the divertor region, SOLPS captures the pressure loss of the helium experiments well; this is shown directly in Figure 12 for the medium-density case, and the modest pressure loss of at most a factor of 2–3 is well-recovered for all time-slices modeled. This implies that the momentum loss due to friction of the plasma with the neutrals in the divertor is well-captured by SOLPS. Further, this has an important implication that, provided one can get the pressure modeled accurately near the X-point (i.e., at the entrance to the divertor), SOLPS provides a good quantitative model of the rest of the divertor to the PFC surface. It should be noted that the neutral density plays an important role in the pressure balance but that direct measurements are lacking at present. Discrepancy in the neutral pressure has also been identified as a contributor to radiation shortfall in ASDEX Upgrade.²⁵ Thus, while the agreement in the electron pressure here is promising, the role of neutral density should be explored more in the future to conclusively assess the sufficiency of this aspect of SOLPS.

The larger discrepancy is seen between the modeling and the values measured upstream near the crown of the

FIG. 12. Poloidal profile of electron pressure for the medium density case with average divertor density matched, including upstream data far from divertor volume.

plasma. As can be seen in Figure 12, the modeled upstream electron pressure is $\sim 50\%$ higher than is measured, as a result of the density discrepancy. This is similar to the “pressure hill” previously observed near the X-point in DIII-D experiments,²⁶ where the electron pressure was measured to be higher than the upstream pressure. However, only the electron contribution to the pressure is measured here, whereas the pressure balance equation involves the total pressure including ion contributions both through the static ion pressure p_i and the dynamic pressure $n_i m_i V_i^2$ due to parallel flow. This suggests that underestimating the ion contribution to the total pressure could be the source of the difficulty in simultaneously matching the divertor and the upstream density.

A missing ion pressure would take the form of either an ion temperature or flow speed being lower in the modeling than is measured in experiment. While, as stated above, ion temperature data are generally not sufficient in resolution to be used in the direct profile fitting procedures employed to match the upstream profile, some ion data are available to compare the modeling to. These measurements are made via charge exchange recombination spectroscopy, and since helium plasmas are under study here direct measurements of the main ion (i.e., helium) temperature are available (rather than relying on impurity ion carbon measurements as is typically done with deuterium plasmas). The ion temperature is indeed measured to be higher than is obtained from the modeling in the far SOL. Of note is that the measured T_i is much higher than T_e , by a factor of nearly ten. Reaching this very high T_i/T_e ratio is very challenging in SOLPS; as a check, even with simulations run with χ_i reduced to $0.01 \text{ m}^2/\text{s}$, T_i was increased only slightly (and not much at all in the far SOL). This is because of strong energy exchange with the electrons: even with radial transport effectively turned off, the ions do not get substantially hotter than the electrons but instead transfer power to the electron channel. It should also be noted that kinetic effects may be quite important for ions in the main SOL, impacting especially the temperature anisotropy and the corresponding interpretation of diagnostics.²⁷

While direct SOL flow measurements were not a focus of this experiment, extensive literature exists on this topic from several tokamak experiments.²⁸ These generally find very strong flows, approaching sonic ($M \sim 0.5$), in the main SOL. 2D fluid models such as SOLPS, on the other hand, predict essentially stagnant plasma flow everywhere outside

of the divertor unless measures are taken to promote strong flows within the code. Reproducing the strong SOL flows measured is complex and requires additional assumptions on the nature of the cross-field transport (e.g., the simultaneous inclusion of an inward pinch velocity and poloidally asymmetric diffusion²⁹). This suggests that strong main SOL flows may also be contributing to the missing upstream pressure inferred from the modeling described here. While neither this nor the discussion of the ion temperature contributions above is conclusive (and is not meant to be so), these results do point to the need for more direct attention on ion temperature and flow in the main SOL, from both the experimental and modeling perspectives.

VI. DISCUSSION AND CONCLUSIONS

These overall results constitute a proof of principle that 2D fluid models such as SOLPS are indeed capable of quantitatively reproducing the radiated power level measured in the divertor. This is an important step, as it implies that the challenge to date in reproducing the radiated power is not universally present due to fundamentally missing physics in the models such as turbulence or strong kinetic effects. The analysis presented here relies heavily on direct electron density and temperature measurements throughout the outer divertor volume made with DTS, and only when these were modeled accurately could radiation shortfall be eliminated. These measurements have allowed the most direct test to date of the radiated power compared to experiment and are arguably required to study topics like the radiation shortfall quantitatively.

The absence of radiation shortfall in helium plasmas is consistent with the ongoing efforts to improve the atomic and molecular physics captured in modeling of deuterium plasmas; these results show that having complete atomic physics can lead to successfully reproducing the radiated power. However, further experiments and modeling of deuterium plasmas are required to show this conclusively, with direct measurements of the main radiating species (both deuterium and carbon emission in the case of the carbon-walled DIII-D). These efforts should include a focus on comparing the neutral density between code and experiment in order to better quantify and benchmark the neutral contributions to power and pressure balance. With carbon walls, carbon will be a major radiator at all divertor temperatures in deuterium plasmas, unlike the helium case, and so future efforts in this area should attempt to quantify both radiation channels³⁰ and compare them to modeling as has been done here. Likewise, the same process of matching the divertor density and temperature profile will be required to conclusively compare radiation in deuterium plasmas. While this is left primarily to future research, we note that previous modeling of DIII-D experiments³¹ showed that the divertor density and temperature could be reasonably matched if the radiated power was artificially scaled to match experiment—consistent with the notion that there are missing contributions in the reaction set used in the modeling.

Finally, these results have also shown that 2D fluid modeling with SOLPS is able to quantitatively describe the

plasma within the divertor but that the connection between the divertor entrance and the upstream SOL remains challenging. This has been worked around in the present modeling by increasing the upstream electron density to values higher than are measured, but future research should aim at better understanding the physics of this missing connection. Ion contributions to the total upstream SOL pressure have been identified as possible deficiencies in the current modeling, and further efforts towards measuring these in experiment and improving their treatment in modeling are warranted. Extending these ion studies to include the divertor region would also be of interest, since a mismatch in the ion parameters within the divertor could also in principle affect the overall comparison between measurement and modeling, for example, through the effect of ion parameters on sputtering yields. The very low carbon emission seen at high densities, however, suggests that these effects are not strong enough to substantially affect the radiation studies described here.

VII. SUMMARY

Experiments and modeling of dissipative divertor operation in helium plasmas at DIII-D have been performed to examine the possible role of molecular physics in the previously observed inability of models to reproduce the measured radiated power. By eliminating the uncertain and complicated molecular physics associated with deuterium, these experiments showed that the radiation can be fully accounted for in modeling. However, this required careful matching of the modeled divertor density to that measured; relying on upstream profile measurements alone (as is typically the case) resulted in lower density in the divertor and consequently lower radiated power than was measured. These results both demonstrate that fluid models are capable of quantitatively describing the divertor under simplified conditions and support the efforts that are ongoing to add the more complicated reactions needed to fully model deuterium divertor physics. Finally, this work has highlighted the need to improve the connection between the midplane and the divertor in the models in order to be able to predict divertor operation for given upstream conditions.

ACKNOWLEDGMENTS

This research was supported by the U.S. DOE under DE-AC05-00OR22725, DE-FC02-04ER54698, and DE-AC52-07NA27344. DIII-D data shown in this paper can be obtained in digital format following the link at https://fusion.gat.com/global/D3D_DMP.

¹A. S. Kukushki, H. D. Pacher, G. Janeschitz, A. Loarte, D. P. Coster, G. Matthews, D. Reiter, R. Schneider, and V. Zhogolev, *Nucl. Fusion* **42**, 187 (2002).

²T. Eich, B. Sieglin, A. Scarabosio, W. Fundamenski, R. J. Goldston, A. Herrmann, and ASDEX Upgrade Team, *Phys. Rev. Lett.* **107**, 215001 (2011).

³R. J. Goldston, *Nucl. Fusion* **52**, 013009 (2012).

⁴M. E. Fenstermacher, S. L. Allen, N. H. Brooks, D. A. Buchenauer, T. N. Carlstrom, J. W. Cuthbertson, E. J. Doyle, T. E. Evans, P.-M. Garbet, R. W. Harvey, D. N. Hill, A. W. Hyatt, R. C. Isler, G. Jackson, R. A. James, R. Jong, C. C. Klepper, C. J. Lasnier, A. W. Leonard, M. A. Mahdavi, R.

- Maingi, W. H. Meyer, R. A. Moyer, D. G. Nilson, T. W. Petrie, G. D. Porter, T. L. Rhodes, M. J. Schaffer, R. D. Stambaugh, D. M. Thomas, S. Tugarinov, M. R. Wade, J. G. Watkins, W. P. West, D. G. Whyte, and R. D. Wood, *Phys. Plasmas* **4**, 1761 (1997).
- ⁵M. E. Fenstermacher, J. Boedo, R. C. Isler, A. W. Leonard, G. D. Porter, D. G. Whyte, R. D. Wood, S. L. Allen, N. H. Brooks, R. Colchin, T. E. Evans, D. N. Hill, C. J. Lasnier, R. D. Lehmer, M. A. Mahdavi, R. Maingi, R. A. Moyer, T. W. Petrie, T. D. Rognlien, M. J. Schaffer, R. D. Stambaugh, M. R. Wade, J. G. Watkins, W. P. West, and N. Wolf, *Plasma Phys. Controlled Fusion* **41**, A345 (1999).
- ⁶V. A. Soukhanovskii, R. Maingi, D. A. Gates, J. E. Menard, S. F. Paul, R. Raman, A. L. Roquemore, M. G. Bell, R. E. Bell, J. A. Boedo, C. E. Bush, R. Kaita, H. W. Kugel, B. P. LeBlanc, D. Mueller, and NSTX Team, *Phys. Plasmas* **16**, 022501 (2009).
- ⁷B. J. Braams, *Contrib. Plasma Phys.* **36**, 276 (1996).
- ⁸A. S. Kukushkin, H. D. Pacher, G. W. Pacher, V. Kotov, R. A. Pitts, and D. Reiter, *J. Nucl. Mater.* **438**, S203 (2013).
- ⁹M. Groth, G. D. Porter, M. E. Rensink, T. D. Rognlien, S. Wiesen, M. Wischmeier, T. Eich, A. Herrmann, S. Jachmich, C. J. Lasnier, H. W. Müller, J. G. Watkins, M. N. A. Beurskens, B. D. Bray, S. Brezinsek, N. H. Brooks, M. E. Fenstermacher, C. Fuchs, A. Huber, A. Kallenbach, A. W. Leonard, A. Meigs, D. L. Rudakov, DIII-D, ASDEX Upgrade Teams, and JET EFDA Contributors, *J. Nucl. Mater.* **415**, S530 (2011).
- ¹⁰J. Roth, *J. Nucl. Mater.* **266–269**, 51 (1999).
- ¹¹D. Moulton, W. Fundamenski, S. Wiesen, G. Corrigan, P. Belo, G. Maddison, C. Giroud, and JET-EFDA Contributors, *J. Nucl. Mater.* **415**, S509 (2011).
- ¹²A. E. Jaervinen, C. Giroud, M. Groth, P. Belo, S. Brezinsek, M. Beurskens, G. Corrigan, S. Devaux, P. Drewelow, D. Harting, A. Huber, S. Jachmich, K. Lawson, B. Lipschultz, G. Maddison, C. Maggi, C. Marchetto, S. Marsen, G. F. Matthews, A. G. Meigs, D. Moulton, B. Sieglin, M. F. Stamp, S. Wiesen, and JET Contributors, *Nucl. Fusion* **56**, 046012 (2016).
- ¹³M. Groth, S. Brezinsek, P. Belo, M. N. A. Beurskens, M. Brix, M. Clever, J. W. Coenen, C. Corrigan, T. Eich, J. Flanagan, C. Guillemaut, C. Giroud, D. Harting, A. Huber, S. Jachmich, U. Kruezi, K. D. Lawson, M. Lehnen, C. Lowry, C. F. Maggi, S. Marsen, A. G. Meigs, R. A. Pitts, G. Sergienko, B. Sieglin, C. Silva, A. Sirinelli, M. F. Stamp, G. J. van Rooij, S. Wiesen, and JET-EFDA Contributors, *Nucl. Fusion* **53**, 093016 (2013).
- ¹⁴S. Wiesen, M. Groth, M. Wischmeier, S. Brezinsek, A. Jarvinen, F. Reimold, L. Aho-Mantila, JET Contributors, The EUROfusion MST1 team, The ASDEX Upgrade team, The Alcator-C-mod team, “Plasma edge and plasma-wall interaction modelling: lessons learned from metallic devices,” *Nuclear Materials and Energy* (in press).
- ¹⁵J. L. Luxon, *Nucl. Fusion* **42**, 614 (2002).
- ¹⁶A. G. McLean, A. W. Leonard, M. A. Makowski, M. Groth, S. L. Allen, J. A. Boedo, B. D. Bray, A. R. Briesemeister, T. N. Carlstrom, D. Eldon, M. E. Fenstermacher, D. N. Hill, C. J. Lasnier, C. Liu, T. H. Osborne, T. W. Petrie, V. A. Soukhanovskii, P. C. Stangeby, C. Tsui, E. A. Unterberg, and J. G. Watkins, *J. Nucl. Mater.* **463**, 533 (2015).
- ¹⁷R. Schneider, X. Bonnin, K. Borrass, D. P. Coster, H. Kastelewicz, D. Reiter, V. Z. Rozhansky, and B. J. Braams, *Contrib. Plasma Phys.* **46**, 3 (2006).
- ¹⁸D. Reiter, M. Baelmans, and P. Boerner, *Fusion Sci. Technol.* **47**, 172 (2005); and See www.eirene.de for information about the EIRENE code.
- ¹⁹M. Wischmeier, D. Coster, X. Bonnin, T. Eich, A. Huber, C. Ingesson, S. Jachmich, A. Kukushin, A. Loarte, G. F. Matthews, R. A. Pitts, J. Rapp, D. Reiter, E. Tsitrone, and Contributors EFDA-JET Work Programme, *J. Nucl. Mater.* **313–316**, 980 (2003).
- ²⁰A. V. Chankin, S. Clement, K. Erents, P. J. Harbour, G. Janeschitz, J. Lingertat, A. Loarte, G. F. Matthews, R. Reichle, P. C. Stangeby, and D. R. Summers, *Plasma Phys. Controlled Fusion* **36**, 1853 (1994).
- ²¹L. Aho-Mantila, S. Potzel, M. Wischmeier, D. P. Coster, H. W. Muller, S. Marsen, A. G. Meigs, S. Muller, M. F. Stamp, S. Brezinsek, ASDEX Upgrade Team, and JET EFDA Contributors, see www.euro-fusionscipu-b.org/wp-content/uploads/2015/04/EFDC140626.pdf for “Assessment of scrape-off layer simulations with drifts against L-mode experiments in ASDEX upgrade and JET,” in 25th IAEA International Conference on Fusion Energy (St. Petersburg, 2014).
- ²²J. M. Canik, R. Maingi, V. A. Soukhanovskii, R. E. Bell, H. W. Kugel, B. P. LeBlanc, and T. H. Osborne, *J. Nucl. Mater.* **415**, S409 (2011).
- ²³P. C. Stangeby, *The Plasma Boundary of Magnetic Fusion Devices* (Institute of Physics, 2000).
- ²⁴S. A. Self and H. N. Ewald, *Phys. Fluids* **9**, 2486 (1966).
- ²⁵F. Reimold, M. Wischmeier, M. Bernert, S. Potzel, D. Coster, X. Bonnin, D. Reiter, G. Meisl, A. Kallenbach, L. Aho-Mantila, U. Stroth, and ASDEX Upgrade Team, *J. Nucl. Mater.* **463**, 128 (2015).
- ²⁶M. J. Schaffer, B. D. Bray, J. A. Boedo, T. N. Carlstrom, R. J. Colchin, C.-L. Hsieh, R. A. Moyer, G. D. Porter, T. D. Rognlien, J. G. Watkins, and DIII-D Team, *Phys. Plasmas* **8**, 2118 (2001).
- ²⁷D. J. Battaglia, K. H. Burrell, C. S. Chang, S. Ku, J. S. deGrassie, and B. A. Grierson, *Phys. Plasmas* **21**, 072508 (2014).
- ²⁸N. Asakura and ITPA SOL and Divertor Topical Group, *J. Nucl. Mater.* **363–365**, 41 (2007).
- ²⁹G. S. Kirnev, G. Corrigan, D. Coster, S. K. Erents, W. Fundamenski, G. F. Matthews, and R. A. Pitts, *J. Nucl. Mater.* **337–339**, 271 (2005).
- ³⁰R. C. Isler, R. W. Wood, C. C. Klepper, N. H. Brooks, M. E. Fenstermacher, and A. W. Leonard, *Phys. Plasmas* **4**, 355 (1997).
- ³¹J. M. Canik, A. R. Briesemeister, C. J. Lasnier, A. W. Leonard, J. D. Lore, A. G. McLean, and J. G. Watkins, *J. Nucl. Mater.* **463**, 569 (2015).