This is an electronic reprint of the original article.
This reprint may differ from the original in pagination and typographic detail.

Nomikos, Nikolaos; Charalambous, Themistoklis; Vouyioukas, Demosthenes; Wichman, Risto; Karagiannidis, George K.

Integrating Broadcasting and NOMA in Full-Duplex Buffer-Aided Opportunistic Relay Networks

Published in:
IEEE Transactions on Vehicular Technology

DOI:
[10.1109/TVT.2020.2999655](https://doi.org/10.1109/TVT.2020.2999655)

Published: 01/08/2020

Document Version
Peer reviewed version

Please cite the original version:
Nomikos, N., Charalambous, T., Vouyioukas, D., Wichman, R., & Karagiannidis, G. K. (2020). Integrating Broadcasting and NOMA in Full-Duplex Buffer-Aided Opportunistic Relay Networks. *IEEE Transactions on Vehicular Technology*, 69(8), 9157-9162. [9107483]. <https://doi.org/10.1109/TVT.2020.2999655>

This material is protected by copyright and other intellectual property rights, and duplication or sale of all or part of any of the repository collections is not permitted, except that material may be duplicated by you for your research use or educational purposes in electronic or print form. You must obtain permission for any other use. Electronic or print copies may not be offered, whether for sale or otherwise to anyone who is not an authorised user.

Integrating Broadcasting and NOMA in Full-Duplex Buffer-Aided Opportunistic Relay Networks

Nikolaos Nomikos, *Member, IEEE*, Themistoklis Charalambous, *Member, IEEE*, Demosthenes Vouyioukas, *Senior Member, IEEE*, Risto Wichman, *Member, IEEE*, and George K. Karagiannidis, *Fellow, IEEE*

Abstract—This paper proposes the integration of non-orthogonal multiple access (NOMA) and broadcasting with buffer-aided (BA) full-duplex (FD) relaying to improve the spectral efficiency of a single-source two-user network. Furthermore, opportunistic relay selection is employed, activating one or two FD relays to support the end-to-end communication. The network performance is improved through buffers, allowing to switch to half-duplex (HD) transmission/reception when FD operation is not feasible. A hybrid BA FD/HD NOMA relay selection algorithm is proposed, herein called BAHyNOMA, orchestrating the three aforementioned techniques, towards a simple yet efficient and robust relay selection. BAHyNOMA is evaluated in terms of outage probability, average sum-rate and average delay, and it is observed that the average sum-rate can be doubled, while maintaining low latency.

Index Terms—Non-orthogonal multiple access, full-duplex, buffer-aided relaying, broadcasting, relay selection.

I. INTRODUCTION

An important technique to improve the quality of wireless transmissions is cooperative relaying. The seminal work of [1] spurred a flurry of research, resulting in novel techniques, such as opportunistic relay selection (ORS) [2] and buffer-aided (BA) relaying (see, e.g., [3], [4] and references therein). Various BA-ORS schemes were proposed [5]–[7] for increased diversity. Recently, broadcasting in the source-relay ($\{S \rightarrow R\}$) links for BA-ORS was proposed in [8], increasing the number of packets at the relays and reducing the delay. In [9], broadcasting led to low-complexity (LoCo) selection with asymmetric links, outdated CSI, and feedback errors.

In order to improve the spectral efficiency, non-orthogonal multiple access (NOMA) has been deployed, where users share the same wireless resources, exploiting channel quality differences [10]. A survey of novel cooperation techniques integrating NOMA, was given in [11]. Thus, relaying and NOMA have been jointly studied in various works. So and Sung in [12] studied user cooperation, where a user performed FD relaying, forming a relay broadcast channel with network coding, improving the achievable rate region. Also, the study in [13] used a dedicated FD relay in a two-user network. Compared to HD, FD operation improved the ergodic sum capacity for low-to-medium signal-to-noise ratio (SNR), even

with residual self-interference (SI). Then, ORS with NOMA was studied in [14], developing two-stage ORS and improving the diversity, compared to conventional max – min ORS.

More recently, NOMA and BA relays were combined in [15] where Luo and Teh proposed adaptive mode selection in a single relay network, switching between NOMA and OMA. Compared to OMA with BA relays and NOMA without BA relays, using this method, the sum-throughput was increased. Then, Zhang *et al.* in [16] proposed adaptive link selection for scenarios with full CSI at the transmitter (CSIT) and no CSIT in the relay-destination ($\{R \rightarrow D\}$) links. The results showed that a diversity gain equal to two can be achieved for buffer sizes larger than two. Finally, Nomikos *et al.* in [17] developed BA-ORS algorithms integrating broadcasting in the $\{S \rightarrow R\}$ link and combining NOMA with OMA for robustness against outages, increasing the average sum-rate and reducing the delay. Furthermore, Nomikos *et al.* in [7] combined HD and FD BA relays with the objective of minimizing the power expenditure. Relay selection among HD and FD operation is decided at the beginning of a transmission frame, consisting of multiple time-slots, by relying on statistical CSI only.

Until now, NOMA and FD have been jointly studied in BA relay networks, as is the case with NOMA and broadcasting. Still, the integration of NOMA, FD and broadcasting in BA ORS has yet to be investigated. So, this work aims to bridge this gap, proposing a BA hybrid FD/HD NOMA ORS algorithm (BAHyNOMA), which has the following features:

- i) $\{S \rightarrow R\}$ broadcasting allows more than one relays to receive the users' signals and CSI overheads are reduced. Additionally, broadcasting when relays have more than one antenna, not only increases the degrees of freedom of ORS, but also allows for combining techniques in which the signals are combined to maximize the received Signal-to-Interference-and-Noise (SINR) ratio;
- ii) BA relays store packets and forward them at a later instant, when FD transmission is not deployed, enabling the BAHyNOMA to seamlessly switch between FD and HD operation, exploiting instantaneous CSI;
- iii) NOMA takes place from the relays to the destinations, considering the users' CSI and the required data rate;
- iv) distributed coordination using timers is adopted, avoiding the shortcomings of centralized network coordination and reducing communication and computational complexity.

Our scheme, BAHyNOMA, was evaluated and was found to achieve twice the average sum-rate compared to HD NOMA and OMA with, additionally, low packet delay.

N. Nomikos and D. Vouyioukas are with the Department of Information and Communication Systems Engineering, University of the Aegean, Samos, Greece. *Emails:* {nnomikos, dvouyiou}@aegean.gr.

T. Charalambous and R. Wichman are with the School of Electrical Engineering, Aalto University, Finland. *Emails:* name.surname@aalto.fi.

G. K. Karagiannidis is with the Department of Electrical and Computer Engineering, Aristotle University of Thessaloniki, Thessaloniki, Greece. *Email:* geokarag@auth.gr.

II. SYSTEM MODEL AND PRELIMINAI

A two-hop network consisting of a source, destinations, D_1 and D_2 , and a cluster $\mathcal{C}$ of K FD forward (DF) relays $R_k \in \mathcal{C}$ ($k \in \{1, \dots, K\}$) and depicted in Fig. 1. Due to severe fading, cc is only established via the relays. Each R_k is equipped with a buffer of size L , where L denotes the maximum number of packets that can be stored. The number of packets in the buffer is denoted by Q_k . Here, a relay either transmits to D_1, D_2 or is in outage and equal buffer allocation is used, i.e., the same amount of packets for D_1 and D_2 .

Time is divided into “frames” of one packet (e.g., fixed-size packets). At any arbitrary time slot, the link $\{i \rightarrow j\}$, the channel coefficient h_{ij} is statistically independent complex normal random variable with zero mean, and variance σ_{ij}^2 , i.e., $h_{ij} \sim \mathcal{CN}(0, \sigma_{ij}^2)$. The channel gains g_{ij} are therefore, exponentially distributed, i.e., $g_{ij} \sim \text{Exp}(\lambda_{ij})$.

A saturated source is assumed and the information rate, r_i , for successful reception at each D_i is fixed and may differ, depending on the application. So, a transmission from a transmitter i to a receiver j is successful, if the SNR Γ_{ij} at the receiver is greater than or equal to the *capture ratio* γ_j . The thermal noise variance at R_k is denoted by σ_k^2 , assumed to be AWGN. At each time-slot, S and/or one of the relays R_k transmits a packet, using a fixed power level P_i , $i \in \{S, R_1, \dots, R_K\}$. As FD relaying is supported, SI exists and $h_{R_k R_k}$ denotes the instantaneous residual SI between the two antennas of relay R_k , following a complex Gaussian distribution and taking values in the range $(0, \sigma_{R_k R_k}^2)$. Retransmissions are based on an Acknowledgements/Negative-Acknowledgements (ACKs/NACKs), where receivers broadcast short-length error-free packets over a separate narrow-band channel.

A link is *feasible* if it is not in outage and fulfills the queue conditions (i.e., for non-full buffers in $\{S \rightarrow R\}$ links and for non-empty buffers in $\{R \rightarrow D\}$ links). Set $\mathcal{F}_{SR}$ contains the relays with feasible $\{S \rightarrow R\}$ links and $\mathcal{F}_{SR}^{\text{tx}}$ contains the relays with feasible $\{S \rightarrow R\}$ links when R_{tx} is transmitting to the destinations (causing inter-relay interference (IRI)). Sets $\mathcal{F}_{RD_1}$ and $\mathcal{F}_{RD_2}$ contain the relays with feasible $\{R \rightarrow D_1\}$ and $\{R \rightarrow D_2\}$ links, respectively. Set $\mathcal{F}_{RD}$ contains the relays that can transmit to both D_1, D_2 , simultaneously.

A. Transmission in the $\{S \rightarrow R\}$ link

In general, D_1 and D_2 might demand a different rate r_ℓ , $\ell \in \{1, 2\}$, and to avoid buffer overflow/underflow, S transmits with rate $r_1 + r_2$ [16]. Since the $K - 1$ relays not transmitting simultaneously with the source have two available antennas for reception it is better to implement an optimum combiner (OC) [18], which combines the diversity branches and maximizes the SINR, allowing for better performance than other techniques, such as maximal-ratio combining (MRC) [19]. The received signal vector $\mathbf{y}_{R_k}$ at relay R_k is given by

$$\mathbf{y}_{R_k} = \mathbf{h}_{SR_k} \sqrt{P_S} x_S + \mathbf{h}_{R_j R_k} \sqrt{P_{R_j}} x_j + \boldsymbol{\eta}_{R_k},$$

Fig. 1. A buffer-aided full-duplex NOMA relay network.

where x_S is the signal transmitted by the source and x is the signal transmitted by the interfering relay R_j . The vector $\mathbf{h}_{i\ell}$ corresponds to the fading coefficients of the links connecting the transmitter i to the antennas of ℓ . Note that the antennas are assumed to be placed distantly enough such that the fading at each antenna is independent from others, i.e., $\mathbb{E}\{\mathbf{h}_{i\ell} \mathbf{h}_{i\ell}^H\} = \mathbf{I}$. Note that if the transmitting relay is also receiving, then $j = k$ and, as expected, only one antenna is available for receiving. Hence, the SINR is given by

$$\Gamma_{SR_j} \triangleq \frac{g_{SR_j} P_S}{g_{R_j R_j} P_{R_j} + \sigma_j^2} \geq \gamma_0 \triangleq 2^{r_1 + r_2} - 1, \quad j \in \mathcal{F}_{RD}.$$

B. Transmission in the $\{R \rightarrow D\}$ link

If a relay R_j is selected, the information symbols of D_1 and D_2 are superimposed and NOMA is performed. Thus, the superimposed information symbol consisting of the symbols x_1 and x_2 of each destination, is defined as $x = \sqrt{\alpha_j} x_1 + \sqrt{1 - \alpha_j} x_2$ with $\mathbb{E}[|x_1|^2] = \mathbb{E}[|x_2|^2] = 1$ and $0 \leq \alpha_j \leq 1$. Then, D_1 will receive an information symbol y_1 containing the desired symbol, as well as the symbol of D_2 , i.e.,

$$y_1 = h_{R_j D_1} \sqrt{\alpha_j P_{R_j}} x_1 + h_{R_j D_1} \sqrt{(1 - \alpha_j) P_{R_j}} x_2 + \eta_1.$$

Similarly, the received information symbol y_2 at D_2 is

$$y_2 = h_{R_j D_2} \sqrt{\alpha_j P_{R_j}} x_1 + h_{R_j D_2} \sqrt{(1 - \alpha_j) P_{R_j}} x_2 + \eta_2,$$

where η_1 and η_2 denote the AWGN at each destination. Since full CSIT is available at the relay, the power allocation coefficient α can be calculated in each time-slot. The value of α is chosen to ensure that the x_1 and x_2 are decoded successfully. For example, for decoding x_2 at both destinations,

$$\Gamma_{R_j D_\ell}(P_{R_j}) = \frac{(1 - \alpha_j) P_{R_j} g_{R_j D_\ell}}{\alpha_j P_{R_j} g_{R_j D_\ell} + \sigma_{D_\ell}^2} \geq \gamma_\ell, \quad \ell \in \{1, 2\}, \quad (1)$$

where $\gamma_\ell \equiv 2^{r_\ell} - 1$. Once x_2 is successfully decoded, x_1 can be decoded interference-free at destination D_1 according to

$$\Gamma_{R_j D_1}(P_{R_j}) = \frac{\alpha_j P_{R_j} g_{R_j D_1}}{\sigma_{D_1}^2} \geq \gamma_1. \quad (2)$$

III. BAHyNOMA: BUFFER-AIDED HALF-DUPLEX/HALF-DUPLEX NOMA SYSTEM

At each time frame, BAHyNOMA is composed of the following steps:

Step 1: After both destinations broadcast a pilot from R_j , assuming reciprocity of the channel [26], find its $\{R \rightarrow D\}$ link with each of the destinations. Then, a power allocation factor α_j for NOMA transmission (§ II-B). After the calculation of α_j is finished (i.e., $\mathcal{F}_{RD}$ is a non-empty set), a relay R_j is selected to be the transmitting relay R_{tx} , with queue length (if more than one relays are in the same maximum queue size, one is chosen at random). This procedure can be implemented in a fully distributed manner with the use of timers [25]: each relay R_j compares the channel by starting a timer whose value is $(Q_j + 1 + \nu_j)^{-1}$, where ν_j is uniformly distributed in $(-0.5, 0.5)$. As a result, the relay whose timer expires first. If more than one relays have the same size, random variable ν_j guarantees different expiration times. So, a flag packet is transmitted by the relay with the largest buffer, notifying the other relays to remain silent, as all the relays are in listening mode during that time. When the flag packet or forwarding information of another relay is sensed by the other relays, they back off. Note that, if $\mathcal{F}_{RD} = \emptyset$, no relay is chosen for transmission.

Step 2: Source S broadcasts the combined signals for D_1 and D_2 with a rate $r = r_1 + r_2$, while the transmitting relay R_j (if there is a feasible one) simultaneously transmits with one of its antennas to the destinations, leading to FD operation, whenever S and R_j are activated at the same time. All the remaining $K - 1$ relays use both of their antennas for receiving the packets broadcasted by the source, thus increasing the number of receiving antennas per relay and, by adopting OC (in which the signals received through the multiple antennas are combined), the SINR is maximized. Relays belonging in $\mathcal{F}_{SR}^{rx}$ receive the source's signal.

Step 3: Once the destinations receive the packets from the transmitting relay R_{tx} and the broadcasting from the source is over, each of them in turn broadcasts an ACK that includes the identity (ID) of the packet received, so that the relays that have stored the same packets in their buffers (due to the source broadcasting) discard them before the beginning of the next time frame, to avoid retransmitting the same packets unnecessarily and clogging up their buffers with obsolete packets. Note that in imperfect conditions where the ACKs are not received by some relays, the overall performance of the network will degrade.

The operation of BAHyNOMA in the duration of a time frame is depicted at Fig. 2.

The procedure followed by each relay R_j in each time frame is given in Algorithm 1.

IV. THEORETICAL ANALYSIS

A. Outage probability

The outage probability for each time frame is defined as the probability that no relays can be selected for transmission or

Fig. 2. Operation of BAHyNOMA during a time frame. The first two parts (called slots herein) take place in Step 1; the source broadcasting, the relay transmitting and the receiving from the relays take place in Step 2 (slot 3); finally, the ACK broadcast from the destinations take place in Step 3 (slot 4).

Algorithm 1 Distributed BAHyNOMA for each relay R_j

- 1: **input** Q_j, ν_j
- Slot 1:**
- 2: listen to the pilots from D_1 and D_2
- 3: use channel reciprocity for acquiring CSI for $\{R_j \rightarrow D_1\}$ and $\{R_j \rightarrow D_2\}$ links
- 4: Selects α_j for NOMA transmission (see (14))
- Slot 2:**
- 5: **if** $R_j \in \mathcal{F}_{RD}$ **then**
- 6: claim transmission using timers, based on the queue size Q_j [25]
- 7: **end if**
- Slot 3:**
- 8: **if** R_j is selected for transmission **then**
- 9: a) use one antenna for reception
- 10: b) use the other antenna to transmit to destinations
- 11: **else**
- 12: use both antennas for reception adopting OC
- 13: **end if**
- Slot 4:**
- 14: discard packets from the buffer based on the ACKs from destinations (if $R_j \neq R_{tx}$)
- 15: **output** Number and IDs of packets in the buffer

reception; analytically, this can be expressed as follows:

$$p_{out} = \mathbb{P} \left\{ \Gamma_{SR_i} < \gamma_0 \quad \forall R_i : Q_i \neq L \right\} \quad (3)$$

$$\cap \left\{ \Gamma_{R_j D_\ell} < \gamma_\ell \text{ for any of } \ell \in \{1, 2\} \quad \forall R_j : Q_j \neq 0 \right\}.$$

The probability of outage ($\Gamma_{SR_j} < \gamma_0$) of the $\{S \rightarrow R_j\}$ link, provided the same relay is transmitting, is given by [7]

$$p_{out\{S \rightarrow R_j | R_j\}} = 1 - \frac{P_S \lambda_{jj}}{P_S \lambda_{jj} + \gamma_0 P_{R_j} \mu_j} \exp \left(-\mu_j \frac{\gamma_0 \sigma_j^2}{P_S} \right), \quad (4)$$

where $\mu_j, \lambda_{jj} > 0 \quad \forall j \in \{1, \dots, K\}$ are obtained from $g_{SR_j} \sim \text{Exp}(\mu_j)$ and $g_{R_j R_j} \sim \text{Exp}(\lambda_{jj})$, where $\mu_j = \sigma_{SR_j}^{-1}/2$ and $\lambda_{jj} = \sigma_{R_j R_j}^{-1}/2$. Since the SI channel gain is assumed known, interference cancellation takes place in FD relays and, hence, the residual SI gain $g_{R_j R_j}$ can be considered to be a lot smaller than the IRI channel gain $g_{R_j R_i}$, $i \neq j$. When there are FD transmissions (and the residual SI is negligible or the transmitting relay is causing no/negligible interference to the receiving relay) or there is no transmission from the relay but still one antenna is used for reception, the distribution simplifies to an exponential distribution, corresponding to the

case where $\lambda_{jj} \rightarrow \infty$ (not used within this paper), i.e.,

$$p_{\text{out}\{S \rightarrow R_j | R_j\}} \equiv p_{\text{out}\{S \rightarrow R_j\}} = 1 - \exp\left(-\mu_j \frac{\gamma_0 \sigma_j^2}{P_S}\right). \quad (5)$$

In case the receiving and transmitting relays differ, it is possible to implement OC with 2 receiving antennas. So, the outage probability ($\Gamma_{SR_i} < \gamma_0$) of the $\{S \rightarrow R_i\}$ link, provided that the transmitting relay is R_j , $j \neq i$, is given by $p_{\text{out}\{S \rightarrow R_i | R_j\}} = \int_0^{\gamma_0} f(\gamma) d\gamma$, where $f(\gamma)$ is the probability density function (pdf) for the SINR distribution (for two receiving antennas and one interferer), given by [20, Eq. (8)]

$$f(\gamma) = \left(1 + \frac{2\bar{P}_{R_j} \left(1 + \frac{\bar{P}_{R_j} \gamma}{2\bar{P}_S}\right)}{1 + \frac{\bar{P}_{R_j} \gamma}{\bar{P}_S}}\right) \frac{\gamma \exp\left(-\frac{\gamma}{\bar{P}_S}\right)}{\bar{P}_S^2 \left(1 + \frac{\bar{P}_{R_j} \gamma}{\bar{P}_S}\right)}, \quad (6)$$

where $\bar{P}_S \triangleq P_S / \mu_i \sigma_i^2$ and $\bar{P}_{R_j} \triangleq P_{R_j} / \lambda_{ji} \sigma_i^2$. Hence, the outage probability is equal to its cumulative distribution function (cdf) and it is given by

$$p_{\text{out}\{S \rightarrow R_i | R_j\}} = 1 - \frac{(\bar{P}_S + \gamma_0 + \gamma_0 \bar{P}_{R_j}) \exp\left(-\frac{\gamma_0}{\bar{P}_S}\right)}{(\bar{P}_S + \bar{P}_{R_j} \gamma_0)}. \quad (7)$$

Remark 1. In case there is no interference, i.e., $P_{R_j} = 0$, (6) becomes $f(\gamma) = \frac{\gamma \exp\left(-\frac{\gamma}{\bar{P}_S}\right)}{\bar{P}_S^2}$, which is a second order Erlang distribution. The outage probability $p_{\text{out}\{S \rightarrow R_i | R_j\}}$ is equivalent to $p_{\text{out}\{S \rightarrow R_i\}}$ and is equal to its cdf, given by [21, Section 1.7.7]

$$p_{\text{out}\{S \rightarrow R_i\}} = 1 - \sum_{n=0}^1 \left(\mu_i \frac{\gamma_0 \sigma_i^2}{P_S}\right)^n \exp\left(-\mu_i \frac{\gamma_0 \sigma_i^2}{P_S}\right). \quad (8)$$

Since the source is broadcasting its packets, the probability of at least one link from the source to any relay R_i not being in outage is thus

$$p_s = 1 - \prod_{i \in \mathcal{C}} p_{\text{out}\{S \rightarrow R_i | R_j\}}. \quad (9)$$

The probability of the transmitting relay R_j to be in outage is to have at least a packet not transmitted to its intended destination. Suppose, as it is the case in Section II-B, x_2 is decoded first and x_1 second. Then, the probability of success of the packets transmitted to D_2 according to (1) and the pdf given in [7] is

$$p_s(D_2) = \frac{1 - \alpha_j}{1 - \alpha_j + \gamma_2 \alpha_j} \exp\left(-\frac{\nu_{j2} \gamma_2 \sigma_2^2}{(1 - \alpha_j) P_{R_j}}\right), \quad (10)$$

where $\nu_{j2} > 0 \forall j \in \{1, \dots, K\}$ are obtained from $g_{R_j D_2} \sim \text{Exp}(\nu_{j2})$. Furthermore, due to NOMA, the probability of success of the packets transmitted to D_1 , require the successful reception of the packets transmitted to D_2 , in the same way as (10), but for the parameters of D_1 according to (1), i.e.,

$$p_{s_1}(D_1) = \frac{1 - \alpha_j}{1 - \alpha_j + \gamma_1 \alpha_j} \exp\left(-\frac{\nu_{j1} \gamma_1 \sigma_1^2}{(1 - \alpha_j) P_{R_j}}\right), \quad (11)$$

and, subsequently, the successful reception of x_1 , according to (2), i.e.,

$$p_{s_2}(D_1) = \exp\left(-\frac{\nu_{j1} \gamma_1 \sigma_1^2}{\alpha_j P_{R_j}}\right). \quad (12)$$

Therefore, the probability of success of the packets transmitted to D_1 is $p_s(D_1) = p_{s_1}(D_1) p_{s_2}(D_1)$. Hence, the outage probability is given by

$$p_{\text{out}\{R_j \rightarrow D_\ell\}} = 1 - p_s(D_1) p_s(D_2). \quad (13)$$

The outage probability is a function of α_j . So, α_j can be chosen to minimize the outage probability. In other words, α_j is the outcome of the following optimization problem:

$$\begin{aligned} \max_{\alpha} \quad & \exp\left(-\frac{\beta_1}{\alpha}\right) \prod_{i=1}^2 \frac{1 - \alpha}{1 - \alpha + \gamma_i \alpha} \exp\left(-\frac{\beta_i}{1 - \alpha}\right), \quad (14a) \\ \text{s.t.} \quad & \alpha \in (0, 1), \quad (14b) \end{aligned}$$

where $\beta_\ell = \frac{\nu_{j\ell} \gamma_\ell \sigma_\ell^2}{P_{R_j}}$, $\ell \in \{1, 2\}$.

Remark 2. From definition (3) for the outage, the overall network is in outage when all links are in outage, i.e.,

$$p_{\text{out}} = \prod_{j \in \mathcal{C}} p_{\text{out}\{R_j \rightarrow D_\ell\}} \prod_{i \in \mathcal{C}} p_{\text{out}\{S \rightarrow R_i | R_j\}}$$

Note that the distributed nature of BAHyNOMA does not allow for evaluating all the combinations before choosing the transmitting relay R_j and, as a consequence, the outage probability of BAHyNOMA will be higher than a centralized approach with information about the instantaneous CSI of all the available links in the network.

B. Diversity order

Before deriving the diversity order¹ of BAHyNOMA, we provide Proposition 1, which basically states that if the source and transmitting relay powers, P_S and $P_{R_{tx}}$ respectively, are large enough (thus not imposing any limitations/constraints), for each feasible (in terms of queue feasibility) pair of relays, R_{rx} (receiving) and R_{tx} (transmitting), then we can find power levels such that interference cancellation conditions are satisfied and the outage probability tends to zero.

Proposition 1 ([9, Proposition 1]).

Let $\sup\{P_S\} = \sup\{P_{R_{tx}}\} = \infty$. For each pair of relays R_{rx} and R_{tx} , there exist P_S and $P_{R_{tx}}$ such that $\text{SNR}_{R_{tx} D_\ell} \geq \gamma_\ell$ and $\text{SINR}_{SR_{rx}} \geq \gamma_0$.

But even without invoking Proposition 1, we can simply consider the cases in which either the $\{S \rightarrow R\}$ link or the $\{R \rightarrow D\}$ link experience no interference. As a result, the outage probability of the network (either when there is successive relaying or a single link transmission) is exponentially distributed and, for symmetric i.i.d. channels, is given by

$$p_{\text{out}\{S \rightarrow R\}} = \varepsilon^K, \quad (15a)$$

$$p_{\text{out}\{R \rightarrow D\}} = \delta^K, \quad (15b)$$

where $\varepsilon \triangleq 1 - \exp(-\beta_0/\phi) - (\beta_0/\phi) \exp(-\beta_0/\phi)$, $\delta \triangleq 1 - a \exp(-\beta_1/\rho) \exp(-\bar{\beta}_1/\rho) \exp(-\beta_2/\rho)$, $a \in (0, 1]$, $\beta_0, \beta_1, \bar{\beta}_1, \beta_2$ are constants, and ϕ and ρ are the power levels of the source and transmitting relay, respectively. The

¹The diversity order (or diversity gain), denoted herein by d , is the gain in spatial diversity, used to improve the reliability of a link and it is defined as follows: $d = -\lim_{\text{SNR} \rightarrow \infty} \frac{\log p_{\text{out}}(\text{SNR})}{\log \text{SNR}}$.

system is in outage when all the links are in c
 $p_{\text{out}} = \varepsilon^K \delta^K$. Therefore, provided the buffer si
 enough, the diversity order of the system is

$$\begin{aligned}
 d &= -\lim_{\phi \rightarrow \infty} \frac{\log p_{\text{out}}\{S \rightarrow R\}}{\log \phi} - \lim_{\rho \rightarrow \infty} \frac{\log p_{\text{out}}\{R \rightarrow D\}}{\log \rho} \\
 &= -K \left[\lim_{\phi \rightarrow \infty} \frac{\log(1 - \exp(-\beta_0/\phi) - (\beta_0/\phi) \exp}{\log \phi} \right. \\
 &\quad \left. + \lim_{\rho \rightarrow \infty} \frac{\log(1 - a \exp(-\beta_1/\rho) \exp(-\bar{\beta}_1/\rho) \exp}{\log \rho} \right] \\
 &\stackrel{(a)}{\approx} -K \lim_{\sigma \rightarrow \infty} \left[\frac{\log(-\beta_0/\sigma)^2}{\log \sigma} + \frac{\log(1 - a + \frac{a(\beta_1}{\sigma})}{\log \sigma} \right] \\
 &\stackrel{(b)}{=} \begin{cases} 2K, & \text{if } 0 < a < 1, \\ 3K, & \text{if } a = 1, \end{cases}
 \end{aligned}$$

where (a) stems from $1 - \exp(-x) \approx x$ (a
 Erlang distribution) and (b) from algebraic

V. NUMERICAL RESULTS

BAHyNOMA is evaluated for $K = 4$ r
 of size of $L = 4$ packets. In the compa
 values correspond to the maximum transmi
 Also, due to non-ideal SIC, the SI channel c
 characterized by $\sigma_{R_k R_k}^2 = 10^{-3} \sigma_{S R_k}^2$ [22
 noise level is equal to 1 mW and the us
 independent non identically distributed (i.n.i
 two users require equal rates $r_1 = r_2 =$
 channel-use (BPCU) and their channel asy
 as $\sigma_{S R_k}^2 = \sigma_{R_k D_1}^2 = 4\sigma_{R_k D_2}^2$. For a fair c
 transmissions are performed with twice the rate, as end-to-end
 communication demands twice the time-slots of NOMA. With
 OMA, D_1 is served in odd time-slots and D_2 in even time-
 slots and outages occur if at two consecutive time-slots all
 the relays fail to successfully transmit/receive. OMA schemes
 include LoCo-Link [9], the $\{R \rightarrow D\}$ prioritization algorithm
 of [24] (OMA RD) and the delay-aware (DA) algorithm of [25]
 (DA-OMA). Furthermore, NOMA versions of the algorithms
 of [24] (NOMA RD) and [9] (DA-NOMA) are considered.
 In NOMA, outages occur if at a given time-slot, no relay can
 transmit/receive. Finally, the hybrid BA-HD-NOMA/OMA of
 [17] is compared, where if the NOMA transmission fails, a
 user is selected in the $\{R \rightarrow D\}$ link to be served with rate r_D .
 BA-HD-NOMA/OMA is not included in the outage results,
 as it cannot be directly compared to NOMA and OMA [16].

In Fig. 3 outage results are given. As D_1 has a stronger
 $\{R \rightarrow D\}$ channel compared to D_2 , NOMA exploits this
 asymmetry through optimal power allocation, outperforming
 OMA. For low transmit power, NOMA and OMA experience
 increased outages, while after 15 dBm performance improves.
 All NOMA schemes offer equal diversity, due to $\{R \rightarrow D\}$
 prioritization, and the same applies to OMA. For high transmit
 power, BAHyNOMA reduces the outages, as FD relaying is
 unaffected by empty buffers.

Fig. 4 depicts the average sum-rate performance. BAHyNOMA
 can double the average sum-rate for high transmit power, while
 for medium transmit power, BA-HD-NOMA/OMA offers the best
 performance, switching to OMA

Fig. 4. Average sum-rate for $K = 4$, $L = 4$ and various algorithms.

in the $\{R \rightarrow D\}$ link, when NOMA fails, and due to its HD
 operation, SI is avoided. Then, for transmit power values
 close to 10 dBm, OMA slightly outperforms NOMA, as the
 interference between the users' signals reduces the probability
 of successful decoding. However, for higher transmit power,
 NOMA surpasses OMA, due to appropriate power allocation.
 Also, in order to provide a clear view on BAHyNOMA's
 performance, its real average power consumption has been
 calculated, including for comparison the HD NOMA RD. So,
 for low transmit power, the two schemes behave similarly and
 their real power consumption is less than the nominal transmit
 power of the nodes, because of frequent outages when the
 transmission is suspended. For higher values, BAHyNOMA's
 FD capability can be exploited without increased power
 consumption, by adopting lower maximum transmit power
 levels than the HD schemes, while achieving higher sum-rate.

Then, the average delay performance is shown in Fig. 5. For
 low transmit power, hybrid BA-HD-NOMA/OMA exhibits
 reduced delay and any differences are due to OMA switch-
 ing and channel asymmetry. As transmit power increases,
 the NOMA schemes reduce the packet delay. Nonetheless,
 compared to hybrid BA-HD-NOMA/OMA, they transmit less
 packets. Moreover, BAHyNOMA performs similar to the
 NOMA schemes, transmitting twice the number of packets
 for high transmit power, due to FD transmissions. Also, since
 packets might not stay in the buffers at all, the average delay
 is reduced to less than one time-slot for high transmit power.

Fig. 5. Average delay for $K = 4$, $L = 4$ and various algorithms.

VI. CONCLUSIONS

In this work, NOMA, BA FD relaying and broadcasting were combined to improve relay selection with low complexity. *NOMA* allowed two users to share the same wireless resources, thus increasing the spectral efficiency of the transmission. *Buffers* enabled the relays to operate in HD mode, when FD was infeasible. Through *broadcasting*, more copies of the same packets are available at the relays' buffers (thus offering increased robustness to the system) and, more importantly, CSIT is not required at the source (thus significantly reducing the implementation complexity). BAHyNOMA was evaluated and was found to achieve twice the average sum-rate compared to HD NOMA and OMA with, additionally, low packet delay.

This work creates a lot of opportunities for the orchestration of NOMA and broadcasting in BA FD networks. Specifically, possible future directions include:

- NOMA/OMA switching can provide performance gains, when the transmission to at least one destination is possible by the relay, thus increasing the sum-rate [17], [27].
- The impact of the direct $\{S \rightarrow D\}$ link should be investigated. As it has been shown in BA OMA relay networks, improved diversity can be harvested [28]. However, in NOMA networks, the interference might result in degradation of the SIC's performance at the destinations.

REFERENCES

- [1] J. N. Laneman, D. N. C. Tse and G. W. Wornell, "Cooperative diversity in wireless networks: Efficient protocols and outage behavior," *IEEE Trans. Inf. Theory*, vol. 50, pp. 3062–3080, Dec. 2004.
- [2] D. S. Michalopoulos and G. K. Karagiannidis, "Performance analysis of single relay selection in Rayleigh fading," *IEEE Trans. Wireless Commun.*, vol. 7, pp. 3718–3724, Oct. 2008.
- [3] N. Nomikos, T. Charalambous, I. Krikidis, D. N. Skoutas, D. Vouyioukas, M. Johansson, C. Skianis, "A survey on buffer-aided relay selection," *IEEE Commun. Surv. & Tut.*, vol. 18, no. 2, pp. 1073–1097, Secondquarter 2016.
- [4] N. Zlatanov, A. Ikhlef, T. Islam and R. Schober, "Buffer-aided cooperative communications: opportunities and challenges," *IEEE Commun. Mag.*, vol. 52, no. 4, pp. 146–153, April 2014.
- [5] A. Ikhlef, D. S. Michalopoulos and R. Schober, "Max-max relay selection for relays with buffers," *IEEE Trans. Wireless Commun.*, vol. 11, pp. 1124–1135, March 2012.
- [6] I. Krikidis, T. Charalambous and J. S. Thompson, "Buffer-aided relay selection for cooperative diversity systems without delay constraints," *IEEE Trans. Wireless Commun.*, vol. 11, pp. 1957–1967, May 2012.

- [7] N. Nomikos, T. Charalambous, D. Vouyioukas, R. Wichman and G. K. Karagiannidis, "Power adaptation in buffer-aided full-duplex relay networks with statistical CSI," *IEEE Trans. Veh. Technol.*, vol. 67, no. 8, pp. 7846–7850, Aug. 2018.
- [8] M. Oiwa and S. Sugiura, "Reduced-packet-delay generalized buffer-aided relaying protocol: Simultaneous activation of multiple source-to-relay links," *IEEE Access*, vol. 4, no., pp. 3632–3646, June 2016.
- [9] N. Nomikos, T. Charalambous, D. Vouyioukas and G. K. Karagiannidis, "Low-complexity buffer-aided link selection with outdated CSI and feedback errors," *IEEE Trans. Commun.*, vol. 66, no. 8, pp. 3694–3706, Aug. 2018.
- [10] L. Lei, D. Yuan, C. K. Ho and S. Sun, "Power and channel allocation for non-orthogonal multiple access in 5G systems: Tractability and computation," *IEEE Trans. Wireless Commun.*, vol. 15, no. 12, pp. 8580–8594, Dec. 2016.
- [11] Z. Ding, X. Lei, G. K. Karagiannidis, R. Schober, J. Yuan and V. K. Bhargava, "A survey on non-orthogonal multiple access for 5G networks: Research challenges and future trends," *IEEE J. Sel. Areas Commun.*, vol. 35, no. 10, pp. 2181–2195, Oct. 2017.
- [12] J. So and Y. Sung, "Improving non-orthogonal multiple access by forming relaying broadcast channels," *IEEE Commun. Lett.*, vol. 20, no. 9, pp. 1816–1819, Sept. 2016.
- [13] C. Zhong and Z. Zhang, "Non-orthogonal multiple access with cooperative full-duplex relaying," *IEEE Commun. Lett.*, vol. 20, no. 12, pp. 2478–2481, Dec. 2016.
- [14] Z. Ding, H. Dai and H. V. Poor, "Relay selection for cooperative NOMA," *IEEE Wireless Commun. Lett.*, vol. 5, no. 4, pp. 416–419, Aug. 2016.
- [15] S. Luo and K. C. Teh, "Adaptive transmission for cooperative NOMA system with buffer-aided relaying," *IEEE Commun. Lett.*, vol. 21, no. 4, pp. 937–940, April 2017.
- [16] Q. Zhang, Z. Liang, Q. Li and J. Qin, "Buffer-aided non-orthogonal multiple access relaying systems in Rayleigh fading channels," *IEEE Trans. Commun.*, vol. 65, no. 1, pp. 95–106, Jan. 2017.
- [17] N. Nomikos, T. Charalambous, D. Vouyioukas, G. K. Karagiannidis and R. Wichman, "Hybrid NOMA/OMA with buffer-aided relay selection in cooperative networks," *IEEE J. Sel. Topics Signal Process.*, vol. 13, no. 3, pp. 524–537, June 2019.
- [18] J. H. Winters, "Optimum combining in digital mobile radio with cochannel interference," *IEEE J. Sel. Areas Commun.*, vol. SAC-2, pp. 528–539, July 1984.
- [19] J. Cui and A. U. H. Skeikh, "Outage probability of cellular radio systems using maximal ratio combining in the presence of multiple interferers," *IEEE Trans. Commun.*, vol. 47, pp. 1121–1124, Aug. 1999.
- [20] Y. Tokgoz, B. D. Rao, M. Wengler and B. Judson, "Performance analysis of optimum combining in antenna array systems with multiple interferers in flat Rayleigh fading," *IEEE Trans. Commun.*, vol. 52, no. 9, pp. 1047–1050, July 2004.
- [21] O. C. Ibe, "Fundamentals of Stochastic Networks," *John Wiley & Sons, Inc.*, Aug. 2011.
- [22] T. Riihonen, S. Werner and R. Wichman, "Hybrid full-duplex/half-duplex relaying with transmit power adaptation," *IEEE Trans. Wireless Commun.*, vol. 10, no. 9, pp. 3074–3085, Sept. 2011.
- [23] T. Baranwal, D. Michalopoulos, and R. Schober, "Outage analysis of multi-hop full duplex relaying," *IEEE Commun. Lett.*, vol. 17, no. 1, pp. 63–66, Jan. 2013.
- [24] Z. Tian, Y. Gong, G. Chen and J. Chambers, "Buffer-aided relay selection with reduced packet delay in cooperative networks," *IEEE Trans. Veh. Technol.*, vol. 66, no. 3, pp. 2567–2575, March 2017.
- [25] N. Nomikos, D. Poulimeas, T. Charalambous, I. Krikidis, D. Vouyioukas and M. Johansson, "Delay- and diversity-aware buffer-aided relay selection policies in cooperative networks," *IEEE Access*, vol. 6, pp. 73531–73547, Nov. 2018.
- [26] M.S. Neiman, "The principle of reciprocity in antenna theory," *Proc. of the IRE*, vol. 31, no.12, pp. 666–671, Dec. 1943.
- [27] M. Alkhawarrah, Y. Gong, G. Chen, S. Lambotharan and J. Chambers, "Buffer-aided relay selection for cooperative NOMA in the Internet of Things," *IEEE Internet Things J.*, vol. 6, no. 3, pp. 5722–5731, June 2019.
- [28] T. Charalambous, N. Nomikos, I. Krikidis, D. Vouyioukas and M. Johansson, "Modeling buffer-aided relay selection in networks with direct transmission capability," *IEEE Commun. Lett.*, vol. 19, no. 4, pp. 649–652, April 2015.