This is an electronic reprint of the original article.

This reprint may differ from the original in pagination and typographic detail.

Romanoff, Jani; Remes, Heikki; Varsta, Petri; Reinaldo Goncalves, Bruno; Kõrgesaar, Mihkel; Lillemäe-Avi, Ingrid; Jelovica, Jasmin; Liinalampi, Sami

Limit state analyses in design of thin-walled marine structures - Some aspects on length-scales

Published in:

JOURNAL OF OFFSHORE MECHANICS AND ARCTIC ENGINEERING

DOI:

[10.1115/1.4045371](https://doi.org/10.1115/1.4045371)

Published: 01/06/2020

Document Version

Peer reviewed version

Published under the following license:

CC BY

Please cite the original version:

Romanoff, J., Remes, H., Varsta, P., Reinaldo Goncalves, B., Kõrgesaar, M., Lillemäe-Avi, I., Jelovica, J., & Liinalampi, S. (2020). Limit state analyses in design of thin-walled marine structures - Some aspects on length-scales. *JOURNAL OF OFFSHORE MECHANICS AND ARCTIC ENGINEERING*, 142(3), [030801].
<https://doi.org/10.1115/1.4045371>

This material is protected by copyright and other intellectual property rights, and duplication or sale of all or part of any of the repository collections is not permitted, except that material may be duplicated by you for your research use or educational purposes in electronic or print form. You must obtain permission for any other use. Electronic or print copies may not be offered, whether for sale or otherwise to anyone who is not an authorised user.

Limit State Analyses in Design of Thin-Walled Marine Structures – Some Aspects on Length-Scales

Jani Romanoff¹

Aalto University, School of Engineering, Department of Mechanical Engineering, Marine Technology

P.O.Box 14300, 00076 Aalto, Finland

jani.romanoff@aalto.fi

Heikki Remes

Aalto University, School of Engineering, Department of Mechanical Engineering, Marine Technology

P.O.Box 14300, 00076 Aalto, Finland

Heikki.remes@aalto.fi

Petri Varsta

Aalto University, School of Engineering, Department of Mechanical Engineering, Marine Technology

P.O.Box 14300, 00076 Aalto, Finland

petri.varsta@aalto.fi

Bruno Reinaldo Goncalves

Aalto University, School of Engineering, Department of Mechanical Engineering, Marine Technology

P.O.Box 14300, 00076 Aalto, Finland

bruno.reinaldogoncalves@aalto.fi

Mihkel Kõrgesaar

Aalto University, School of Engineering, Department of Mechanical Engineering, Marine Technology

P.O.Box 14300, 00076 Aalto, Finland

mihkel.korgesaar@aalto.fi

Ingrit Lillemäe-Avi²

Meyer Turku Shipyard

Telakkakatu 1, 20240 Turku, Finland

ingrit.lillemae@gmail.com

¹ Corresponding author, Tel. +358 50 511 3250.

² Currently LTH Baas, Tuukri 5, 10120 Tallinn, Estonia

Jasmin Jelovica

The University of British Columbia, Department of Mechanical Engineering
2054 - 6250 Applied Science Lane, Vancouver, BC Canada V6T 1Z4
jjelovica@mech.ubc.ca

Sami Liinalampi

Aalto University, School of Engineering, Department of Mechanical Engineering, Marine Technology
P.O.Box 14300, 00076 Aalto, Finland

ABSTRACT

Present paper gives an overview of the factors that affect the strength and structural design of advanced thin-walled marine structures with reduced plate thickness or alternative topologies to those used today in marine industry. Due to production-induced initial deformations and resulting geometrical non-linearity, the classical division between primary, secondary and tertiary responses becomes strongly coupled. Volume-averaged, non-linear response of structural element can be used to define the structural stress strain relation that enables analysis at the next, larger, length scale. This, today's standard homogenization process needs to be complemented with localization, where the stresses are assessed at the details, such as welds for fatigue analysis. Due to this, the production-induced initial distortions need to be considered with high accuracy. Another key question is the length-scale interaction in terms of continuum description. Non-classical continuum mechanics are needed when consecutive scales are close. Strain-gradients are used to increase the accuracy of the kinematical description of beams, plates and shells. The paper presents examples of stiffened and sandwich panels covering limit states such as fatigue, non-linear buckling and fracture.

INTRODUCTION

Lightweight design is essential for marine structures. Trend towards sustainable use of natural resources has strengthened the position of steel as structural material. The fuel efficiency requirements of ships calls for alternative structural topologies with

reduced plate thicknesses. However, the strength assessment cause challenges as the related design limits and criteria are at their infancy. The major issues are the increased initial distortions and changes in the production process that can lead for example changes in weld geometry and strength properties. Initial deformations in slender structure require geometrically non-linear structural analyses. On the other hand, the stress-based fatigue assessment methods are typically related to certain assumptions in weld geometry and plate thickness. Thus, design methods need to be developed further to allow implementation of these improved structures to practice.

Due to production-induced initial deformations and resulting geometrical non-linearity, the classical division for linear structures, between primary, secondary and tertiary responses become coupled. In this coupling, there are two major issues. One is the process of homogenization and localization of stresses at the level of structural member, e.g. stiffened panel. Homogenized properties are needed at the larger length scale to accelerate the analysis times, e.g. transition from panel to hull girder level; see for example Refs. [1-11]. This volume-averaged structural stress-strain relation can be used to assess responses at larger scale that allows for example investigations on strength and load-carrying mechanism at this level. However, often the failure initiates at the lower length scales and is affected by the multiaxiality of the loading. Therefore, localization process is needed to estimate the stresses at lower scale, when the responses at larger scale are known; see for example Refs. [12-14]. Another key question is the length-scale interaction in terms of continuum description. In homogenisation-localisation process, a fundamental assumption is that the length scales

are clearly separable, i.e. $l_{\text{primary}} \gg l_{\text{secondary}} \gg l_{\text{tertiary}}$, where the l is the characteristic length of deformation or stress at the corresponding scale. In marine structures this assumption can be violated. Therefore, non-classical continuum mechanics [15,16] are needed. Strain-gradients and couple stresses are used to increase the accuracy of the kinematical description of beams, plates and shells [17-20] based on equivalent single layer theory (ESL).

Present paper gives an overview of the factors that affect the strength and structural design of advanced thin-walled marine structures with reduced plate thickness or alternative topologies to those used today in marine industry. First some challenges and solutions in the response prediction are presented that allow reliable transition between the length scales. Then we present the same for ultimate strength assessment where we limit ourselves to ductile fracture and non-linear buckling, where the load-end-shortening curves are derived for tension and compression respectively in volume-average sense. Next, we present the fatigue assessment where the localization of stresses is important. We show the similarities and extensions to the theories and approaches that have been utilized over recent decades in analysis and design of marine structures. The examples of this paper are selected from stiffened and sandwich panels made from steel.

RESPONSE PREDICTION

One of the main obstacles for introduction of thin-walled structures to ship structures are due to the production-induced initial distortions and residual stresses,

residual stresses are omitted here to clarify the concepts. Structural design is carried out often by clearly splitting the response evaluation to primary, secondary and tertiary levels. When the scales are clearly separated in terms of characteristic length of stress or displacement, i.e. $l_{\text{primary}} \gg l_{\text{secondary}} \gg l_{\text{tertiary}}$, one can assess the stress strain relation for larger scale by using the actual geometry and material of the structure at the lower scale and by computing the relation under certain load and boundary conditions at the edges of the model, i.e. by utilizing Representative Volume Element (RVE). This process of homogenization is widely used in marine technology as the concept of load-end-shortening curves and in materials science as concept of multi-scale modeling.

It is clear that the non-linear response depends on the adopted load and boundary conditions at the edges of the RVE as well as the initial imperfections and residual stresses. One fundamental assumption in homogenization is the periodicity assumption, i.e. $f(x) = f(x + l_{\text{scale}})$. This means that the deformation and stress at the opposite edges of the RVE must be equal. In marine structures, with geometrically complex shape and topology, this assumption can get violated easily. In order to fix the problem, extended, non-local continuum theories have been developed where the strain at the point is not dependent only on the strain at the same points, but also by its gradients. In the couple stress -based theory, the first gradient of deformation is included into the strain description. This gradient is evaluated at the unit cell reference point, located at the center of the unit cell. In this location the homogenized and periodic solutions are assumed to be equal. In practice, this means that the RVE can be exposed to in-plane bending in addition to the classical pure tensile and shear

components. This allows improved accuracy in response predictions for wider range of applications. Example of this is shown in Fig. 1, where a beam in 3-point bending is computed using continuum based modified couple stress Timoshenko beam theory as given in Reddy [17] and compared to 3D-FEA of the periodic beam. As figure shows, the deflection and stress is in excellent agreement even though the scales are close, i.e.

$I_{secondary}=4I_{tertiary}$. It is also seen that as the rotation stiffness (and shear stiffness) approaches zero, the classical Timoshenko beam theory fails to predict correctly the deflections while the enhanced theory predicts it correctly.

When continuum description is accurate, the next issue to tackle is transition between the scales when the details are included into the analysis, see the simple linear example from Fig. 2. There, the lightweight design is made by the steel sandwich panels, that calls for asymmetric, single-sided, joining when production issues are highlighted. From theory of thin-walled structures it is known that the membrane action of the panel should dominate over the bending when the panel is far from the neutral axis of the ship. Then the only design parameter that should define the stiffness of the structure, i.e. load-end-shortening curve, is the product of Young's modulus, E , and cross-sectional area, A , of the stiffened panel, i.e. EA . Fig. 2 shows that even though the asymmetry is very local and only induced by the joint between panels (distance around $I_{secondary}=10^1m$), the response of the entire hull girder is affected when normal stresses due to primary bending are assessed ($I_{primary}=30I_{secondary}$). This phenomenon is of course affected by the level of asymmetry of the panel and more specifically the coupling between membrane and bending, i.e. **ABD**-matrix, of the stiffened panel element

(**A**=extension, **B**=extension bending coupling, and **D**=bending). The example given here has strong coupling which is very local and periodic in the hull girder. This could be identified as *topological periodicity* in otherwise prismatic structure. In order to handle this in structural analysis, the full ABD-matrix should be used instead of the intuitive and often only used A-matrix. This adds computational efforts, but is needed for accuracy.

It is clear for this linear case that the continuum description results in accurate responses, but the level of modeling details must be right to get reliable results. The situation changes when we extend the investigation to geometrically non-linear two-scale analysis in the same ship but use traditional stiffened panels, See Fig. 3. Now the initial panel geometry is prismatic, but the production-induced initial imperfections introduce *geometrical periodicity* to the panel, where the length of periodicity is in the order of magnitude of stiffener spacing i.e. $l_{scale} \approx 100\text{m}$ [21,22]. The initial imperfections are assumed to have sinusoidal shape as commonly assumed in the analysis of marine structures and the amplitude is varied. It is seen that the load shifts away from the plates to stiffeners as the amplitude increases, but this shift is modest in comparison to the sandwich panel case and seen to have significant effect only in cases beyond current IACS recommendations. The same phenomena are seen in Fig. 1b, but caused in that case due to periodicity in the location of joints. The key issue in both cases is that the nominal load level, i.e. membrane stress, at the decks is not uniform, has periodicity due to membrane-bending coupling, and this periodicity is affected by the boundary conditions for both membrane and bending action.

ULTIMATE STRENGTH

In ultimate strength, the key issue is the structural stress-strain relation, i.e. the load-end-shortening curve. From the viewpoint of the response of larger scale, the focus is on volumetric average response. Roughly idealizing situation, the tensile and compressive responses are needed for each structural element in the hull girder as is done in Smith's method. However, as the response is two-dimensional we have made attempts here to formulate these approaches directly to plate-level model. This limits the investigations to ductile fracture in tension and post-buckling until first-fiber yield in compression. This is due to the fact that in periodic plates, the yielding is caused by stress-resultants, which can change in magnitude non-proportionally as the applied load increases. This situation is due to the membrane-bending coupling. On the other hand, the ABD-stiffness matrix is affected by yielding. Thus, further research is needed on modeling of the full 2-way coupling.

Ductile fracture is affected by the stress triaxiality and shell element size. Recent investigations from collision and grounding research and on material failure [24-28] are used by Körgeaar and co-workers [29] to formulate the structural stress strain relation to panel level. We limit the investigations to the panel level membrane responses. As Fig. 4 shows the panel level responses can be obtained very accurately with non-linear extension stiffness matrix, i.e. **A**-matrix, even in cases where there is a deck opening. The anisotropic, non-linear, **A**-matrix in this case is computed using analytical equations and Rule-of-Mixtures.

In compression the extension matrix, **A**-matrix, is not enough as the panel fails locally for example by buckling of the plates inside RVE. This means that the full **ABD**-matrix is needed where all terms can be non-linear. Instead of the analytical approaches this matrix is derived numerically using sub models and periodic boundary conditions that follow assumptions of classical continuum mechanics, see Fig. 5. In this approach the unit cell of the panel is exposed to membrane and bending strains according to First order Shear Deformation theory. The stress resultants are evaluated at unit cell borders. The comparison of strain and curvatures and the resulting stress resultants gives the full **ABD**-matrix. It should be noted that the sequence of applying membrane and bending strains will have an effect on the stiffnesses due to unit cell buckling. This makes the **ABD**-matrix non-symmetric which increases the computational efforts. Furthermore, as the compressive surface in RVE is shortened and tensile elongated, the RVE changes shape and size for changing load. Therefore, we obtain in this case 3rd type of length scale interaction, what we call here *progressive periodicity*. As the results in Fig. 5 show the accuracy of the panel post-buckling response prediction is very accurate. However, the true test of the method is in analysis of large structures, where the primary, secondary and tertiary scales are coupled all at the same time. For this type of investigation, we present in Fig. 6, a typical benchmark example of a box-beam in 4-point-bending [30-33] with web-core steel sandwich panel as shell structures [34].

Fig 6. presents that when full coupling between the scales is considered the local, normalized load-end-behavior of the deck that buckles is very accurately predicted by the equivalent single layer mesh and that the full two-scale coupling is not always

needed and linear micro-structural modeling is enough when unit cells are sturdy in comparison to macro-scale responses. However, it should be mentioned that the eigenvalue buckling might wrongly predicted if the corner regions are not properly modelled (i.e. overlapping material). It should be also mentioned here that the computational savings are enormous as the solution with ESL requires around 64 times less memory than 3D FEA and the analysis is carried out in hours rather than in days (in case of 3D-FEA). This computational saving is due to the fact that local failure defines the required times step in FEA which significantly lowers the computational speed at the moment of local failure; this relates to characteristic lengths of buckling, i.e.

$l_{secondary} \gg l_{tertiary}$, where the effect of tertiary buckling length is included to pre-computed load-end-shortening curve.

FATIGUE ANALYSIS

While ultimate strength analysis focuses on volumetric average and load-end-shortening curve, in the fatigue assessment detail level response is the decisive factor. In structural analysis preference is on stress-based methods with material linearity assumption being valid. This assumption is justified as the stress is at maximum mildly non-linear, only at the very small volume of the structure when the design is focused on medium high cycle and high cycle fatigue regions. Another assumption commonly utilized is that the secondary and primary responses are accurately obtained by the undistorted, initial, idealized geometry of the panel and the weld. However, when thickness of the plates is reduced and geometry of the welds changes (for example to

stake-welds), this assumption becomes one of the sources of uncertainty to the analysis [21,23,36-41]; this result is indicated also in Figures 2 and 3. Therefore, research have been carried out by (see Fig. 7), measuring the actual shapes of the produced structures, building very detailed shell-element based finite element models, and by carrying out the detailed comparison between measured and computed stresses at fatigue critical locations.

The investigations show that by this sequence [22,42] the stress and displacement responses are accurately captured and the scatter between fatigue tests at full- and component scales is reduced to practically non-existent see Fig. 8. The challenge however, from viewpoint of structural design is that the periodicity of the distorted plate is valid assumption only for deflections, but not necessarily on slopes and higher order derivatives of the displacement field (i.e. $d^n x/dx^n$, $n=1,2,\dots$). This means that the homogenization for stresses, that are based on higher order derivatives, can lead to erroneous results unless also the derivatives are periodic. Due to this localization process, use of trigonometric functions to describe initial imperfections becomes questionable. In real structures, this condition is almost always violated and 3D-shell element models are needed when fatigue is assessed

CONCLUSIONS AND DISCUSSION

Present paper gave an overview of the factors that affect the strength and structural design of advanced thin-walled marine structures with reduced plate thickness [21-22,38,40-42] or alternative topologies to those used today in industry [43-

45]. Due to production-induced initial deformations and resulting geometrical non-linearity, the classical division between primary, secondary and tertiary responses become strongly coupled. This calls for structural design methods that link the traditionally separate field of fatigue [23,46] and ultimate limit state assessments Refs. [2,9] under one umbrella.

The ultimate strength is often assessed by using the volume-averaged, non-linear response of structural element [2,9,47,48]. This structural stress strain relation enables analysis at the next, larger, length scale. In the analysis of thin-walled structures this standard homogenization process needs to be complemented with localization, where the stresses are assessed at the details, such as welds for fatigue analysis [12-14,49]. Analogous to multi-scale modeling, field of engineering science that develops fast in material science [12-13,50] these two processes are needed to be fully coupled to move to the next level of engineering computations. This also requires that the production-induced initial distortions need to be considered with much higher accuracy than in case of before. With today's measuring and simulations tools, the actual geometry of the produced structure can be measured in detail and fed to the finite element analysis to assess the structural response for example in ship's service [22]. In this type of work, it is essential to understand the length-scales associated with the structural assessment. The paper discussed about *topological* (spacing of joints), *geometrical* (initial distortions) and *progressive* (developing distortions) length-scale interactions. In cases where homogenization is used to reduce the size of computational models it is important to understand these effects in terms of continuum description.

Non-classical continuum mechanics are needed when the order of magnitude of the consecutive scales is not clearly separable [15-19,51]. Strain-gradients and couple stresses were used to increase the accuracy of the kinematical description of beams, plates and shells where the consecutive length scales are close [19,52,53]. As strain-gradients are also widely used to explain localization of plasticity, the formulations could be extended to this direction too [19,51,54-57]. All this is left for future work.

ACKNOWLEDGMENT

The work has been motivated by the scientific career of Professor Carlos Guedes Soares, the distinguished professor from Instituto Superior Technico, Lisbon Portugal. His scientific contribution covers a lot of topics, approaches and ideas that have been exploited in present paper. Thus, his contribution to field of marine structures is highly appreciated. The work reported here has been carried out in numerous national and EU-funded projects which results are presented in references below. There the acknowledgements to the companies involved in the development work is acknowledged.

NOMENCLATURE

f	Any function
l	Characteristic length
A	Extension stiffness matrix
B	Extension-bending coupling stiffness matrix
D	Bending stiffness matrix
N	Normal force
M	Bending moment

REFERENCES

- [1] Caldwell, J.B. "Ultimate Longitudinal Strength." Transaction of RINA. Vol. **107** (1965): pp. 411-430.
- [2] Faulkner, D. "A Review of Effective Plating for the Analysis of Stiffened Plating in Bending and Compression." Journal of Ship Research. Vol. **19** No.1 (1975): pp 1-17.
- [3] Smith, C.S. "Influence of local compressive failure on ultimate longitudinal strength of a ship's hull." Proceedings of the 1st International Conference on Practical Design of Ships and other floating structures, PRADS. Tokyo, 1977: p. 73–79.
- [4] Dow, R.S., Hugill, R.C., Clark, J.D and Smith, C.S. "Evaluation of Ultimate Ship Hull Strength." Extreme Loads Response Symposium, SNAME (1981).
- [5] Guedes Soares, C. and Soreide, T.H. "Behaviour and Design of Stiffened Plates Under Predominantly Compressive Loads." International Shipbuilding Progress Vol. **30** No. 341 (1983): pp. 13-27.
- [6] Gordo, J.M., and Guedes Soares, C. "Approximate methods to evaluate the hull girder collapse strength", Marine Structures, 1996, Vol. **9**(3), pp. 449-470. DOI 10.1016/0951-8339(95)00030-5
- [7] Paik, J.K., Thayamballi, A.K. and Jung, S.C. "Ultimate strength of ship hulls under combined vertical bending, horizontal bending, and shearing forces." Trans. SNAME. Vol. **104** (1996): pp. 31-59.
- [8] Sadovský, Z., Teixeira, A.P. and Guedes Soares, C. "Degradation of the compressive strength of square plates due to initial deflection." Journal of Constructional Steel Research. Vol. **62** (2006): pp. 369-377. DOI 10.1016/j.jcsr.2005.07.013
- [9] Paik, J.K. "Some recent advances in the concepts of plate-effectiveness evaluation." Thin-Walled Structures. Vol. **46** (2008): pp. 1035-1046. DOI 10.1016/j.tws.2008.01.022
- [10] Xu, M.C., and Guedes Soares, C. "Assessment of the ultimate strength of narrow stiffened panel test specimens." Thin-Walled Structures. Vol. **55** (2012): pp. 11-21. DOI 10.1016/j.tws.2012.02.006
- [11] Xu, M.C., and Guedes Soares, C. "Comparisons of calculations with experiments on the ultimate strength of wide stiffened panels." Marine Structures. Vol. **31** (2013): pp. 82-101. DOI 10.1016/j.marstruc.2013.01.003

- [12] Geers, M.G.D., Kouznetsova, V.G. and Brekelmans, W.A.M. "Multi-scale computational homogenization: Trends and challenges." *Journal of Computational and Applied Mathematics*. Vol. **234** (2010): pp. 2175-2182. DOI 10.1016/j.cam.2009.08.077
- [13] Miehe, C., Schröder, J. and Becker, M. "Computational homogenization analysis in finite elasticity: material and structural instabilities on the micro- and macro-scales of periodic composites and their interaction." *Computer Methods in Applied Mechanics and Engineering*. Vol. **191** (2002): pp. 4971-5005. DOI 10.1016/S0045-7825(02)00391-2
- [14] Romanoff, J. and Varsta, P., "Bending response of web-core sandwich plates." *Composite Structures*. Vol. **81** No. 2 (2007): pp. 292-302. DOI 10.1016/j.compstruct.2006.08.021
- [15] Mindlin, R.D. "Micro-structure in linear Elasticity" Department of Mechanical Engineering, University of British Columbia, 1963.
- [16] Eringen, A.C. "Nonlocal Polar Elastic Continua." *International Journal of Engineering Sciences*. Vol. **10** No. 1 (1972): pp. 1-16.
- [17] Reddy, JN. "Microstructure-dependent couple stress theories of functionally graded beams." *Journal of the Mechanics and Physics of Solids*. Vol. **59** (2011): pp. 2382-2399. DOI 10.1016/j.jmps.2011.06.008
- [18] Romanoff, J. and Reddy, J.N., "Experimental Validation of the Modified Couple Stress Timoshenko Beam Theory for Web-core Sandwich Panels." *Composite Structures*. Vol. **111** (2014): pp. 130-137. DOI 10.1016/j.compstruct.2013.11.029
- [19] Romanoff, J., Reddy, JN and Jelovica, J. "Using non-local Timoshenko beam theories for prediction of micro- and macro-structural responses." *Composite Structures*. Vol. **156** (2016): pp. 410-420. Ref. a. DOI 10.1016/j.compstruct.2015.07.010
- [20] Romanoff, J., Jelovica, J., Avi, E., Reinaldo Goncalves, B., Körgesaar, M., Raikunen, J., Remes, H., Niemelä, A., Reddy, JN and Varsta, P. "Use of a Equivalent Single Layer Plate Theory in Ship Structural Design." *Proceedings of PRADS2016 4th – 8th September, 2016 Copenhagen, Denmark*. Ref. b.
- [21] Eggert, L., Fricke, W., Paetzhold, H. "Fatigue strength of thin-plated block joints with typical shipbuilding imperfections." *Welding in the World*. Vol. **56** No. 11-12 (2012): pp. 119-128.
- [22] Lillemäe, I., Liinalampi, S., Remes, H., Itävuori, A., and Niemelä, A. "Fatigue strength of thin laser-hybrid welded full-scale deck structure." *International Journal of Fatigue*. Vol. **95** (2017) pp. 282–292. DOI 10.1016/j.ijfatigue.2016.11.012

- [23] Remes, H., Romanoff, J., Lillemäe, I., Frank, D., Liinalampi, S. and Lehto, P. and Varsta, P. "Factors affecting the fatigue strength of thin-plates in large structures." *International Journal of Fatigue*. Vol. **101**, No. 2 (2017): pp. 397-407. DOI 10.1016/j.ijfatigue.2016.11.019
- [24] Ehlers, S. and Varsta, P. "Strain and stress relation for non-linear finite element simulations." *Thin-Walled Structures*. Vol. **47** No 11 (2009): pp. 1203-1217. DOI 10.1016/j.tws.2009.04.005
- [25] Körgesaar, M. and Romanoff, J. "Influence of Softening on Fracture Propagation in Large-Scale Shell Structures." *International Journal of Solids and Structures*. Vol. **50** (2013): pp. 3911–3921. DOI 10.1016/j.ijsolstr.2013.07.027
- [26] Hogström P. and Ringsberg, J.W. "An extensive study of a ship's survivability after collision - a parameter study of material characteristics, non-linear FEA and damage stability analyses." *Marine Structures*. Vol. **27** (2012): pp. 1–28. DOI 10.1016/j.marstruc.2012.03.001
- [27] Ehlers, S. "Strain and stress relation until fracture for finite element simulations of a thin circular plate." *Thin-Walled Structures*. Vol. **48** No. 1 (2010): pp. 1-8. DOI 10.1016/j.tws.2009.08.004
- [28] Körgesaar, M., Remes, H. and Romanoff, J. "Size dependent response of large shell elements under in-plane tensile loading." *International Journal of Solids and Structures*. Vol. **51** No. 21-22 (2014): pp. 3752-3761. DOI 10.1016/j.ijsolstr.2014.07.012
- [29] Körgesaar, M., Reinaldo Goncalves, B., Romanoff, J. and Remes, H. "Behaviour of orthotropic web-core steel sandwich panels under multi-axial tension." *International Journal of Mechanical Sciences*. Vol. **115-116** (2016): pp. 428–437. DOI 10.1016/j.ijmecsci.2016.07.021
- [30] Dowling, P.J., Chatterjee, S., Frieze, P. and Moolani, F.M. "Experimental and predicted collapse behaviour of rectangular steel box girders." *International Conference on Steel Box Girder Bridges*. (1973) London.
- [31] Gordo, J.M. and Guedes Soares, C. "Experimental Evaluation of the Ultimate Bending Moment of a Box Girder." *Marine Systems and Offshore Technology*. Vol. **1** No. 1 (2004): pp. 33–46.
- [32] Gordo, J.M. and Guedes Soares, C. "Tests on ultimate strength of hull box girders made of high tensile steel." *Marine Structures*. Vol. **22** No. 4 (2009): pp. 770–790. DOI 10.1016/j.marstruc.2009.07.002

- [33] Gordo, J.M. and Guedes Soares, C. "Experimental Evaluation of the Ultimate Bending Moment of a Slender Thin-walled Box Girder." *Journal of Offshore Mechanics and Arctic Engineering*. Vol. **137** No. 2 (2015): 021604. DOI 10.1115/1.4029536
- [34] Metsälä, M., "Geometrically Nonlinear Bending Response of Steel Sandwich Box Girder Using Equivalent Single Layer Theory." M.Sc. Thesis. Aalto University, School of Engineering. 2016.
- [35] Reinaldo Goncalves, B., Jelovica, J. and Romanoff, J. "A homogenization method for geometric nonlinear analysis of sandwich structures with initial imperfections." *International Journal of Solids and Structures*. Vol. **87** No. 1 (2016): pp. 194-205. DOI 10.1016/j.ijsolstr.2016.02.009
- [36] Chakarov, K., Garbatov, Y. and Guedes Soares, C. "Fatigue analysis of ship deck structure accounting for imperfections." *International Journal of Fatigue*. Vol. 30 No. 10–11 (2008): pp. 1881-1897. DOI 10.1016/j.ijfatigue.2008.01.015
- [37] Frank, D., Romanoff, J. and Remes, H. "Fatigue strength assessment of laser stake-welded web-core steel sandwich panels." *Fatigue & Fracture of Engineering Materials & Structures*. Vol. **36** (2013): pp. 724–737. DOI 10.1111/ffe.12038
- [38] Fricke, W. and Feltz, O. "Factors between small-scale specimens and large components on the fatigue strength of thin-plated block joints in shipbuilding." *Fatigue and Fracture of Engineering Materials & Structures*. Vol. **36** No. 12 (2013): pp. 1223-1231. DOI: 10.1111/ffe.12058
- [39] Fricke, W., Remes, H., Feltz, O., Lillemäe, I., Tchuindjang, D., Reinert, T., Nevierov, A., Sichermann, W., Brinkmann, M., Kontkanen, T., Bohlmann, B. and Molter, L. "Fatigue strength of laser-welded thin-plate ship structures based on nominal and structural hot-spot stress approach." *Ships and Offshore Structures*. Vol. **10** No. 1 (2015): pp. 39–44. DOI 10.1080/17445302.2013.850208
- [40] Hashemzadeh, M. Garbatov, Y. and Guedes Soares, C. "Analytically based equations for distortion and residual stress estimations of thin butt-welded plates", *Engineering Structures*. Vol. **137** (2017): pp. 115-124. DOI 10.1016/j.engstruct.2017.01.041
- [41] Lillemäe-Avi, I., Remes, H., Dong, Y., Garbatov, Y., Quéméner, Y., Eggert, L., Sheng, Q. and Yue, J. "Benchmark study on considering welding-induced distortion in structural stress analysis of thin-plate structures", *Proceedings of MARSTRUCT 2017 – progress in the analysis and design of marine structures*, Lisbon, Portugal, May 8th – 10th 2017, CRC Press, London, pp. 387-394.

- [42] Lillemäe, I., Lammi, H., Molter, L. and Remes, H. "Fatigue strength of welded butt joints in thin and slender plates." *International Journal of Fatigue*. Vol. **44** (2012): pp. 98-106. DOI 10.1016/j.ijfatigue.2012.05.009
- [43] Roland, F. and Reinert, T. "Laser Welded Sandwich Panels for the Shipbuilding Industry." *Lightweight Construction – Latest Developments*, February 24-25, 2000, London, SW1, pp. 1-12.
- [44] Marsico, T.A., Denney, P. and Furio, A., "Laser-Welding of Lightweight Structural Steel Panels". *Proceedings of Laser Materials Processing Conference ICALEO 1993*, pp. 444-451.
- [45] Romanoff, J., Ehlers, S. and Remes, H., "Influence of Nonsymmetric Steel Sandwich Panel Joints on Response and Fatigue Strength of Passenger Ship Deck Structures." *Journal of Ship Production and Design*. Vol. **32** (2016): pp. 1–9. [dx.doi.org/10.5957/JSPD.32.3.150018](https://doi.org/10.5957/JSPD.32.3.150018)
- [46] Fricke, W. "Review: Fatigue of welded joints: state of development." *Marine Structures*. Vol. **16** (2003): pp. 185-200.
- [47] Byklum, E., and Amdahl, J. "A simplified method for elastic large deflection analysis of plates and stiffened panels due to local buckling." *Thin-walled Structures*. Vol. **40** (2002): pp. 925-953.
- [48] Byklum, E., Steen, E. and Amdahl, J. "A semi-analytical model for global buckling and postbuckling analysis of stiffened panels." *Thin-walled Structures*. Vol. **42** (2004): pp. 701-717.
- [49] Frank, D., Romanoff, J. and Remes, H. "Fatigue strength assessment of laser stake-welded web-core steel sandwich panels." *Fatigue & Fracture of Engineering Materials & Structures*. Vol. **36** (2013): pp. 724-737. DOI 10.1111/ffe.12038.
- [50] Matousz, K., Geers, M.G.D., Kouznetsova, V.G. and Gillmann, A. "A review of predictive nonlinear theories for multiscale modeling of heterogeneous materials." *Journal of Computational Physics*. Vol. **330** (2017): pp. 192-220.
- [51] Srinivasa, A.R. and Reddy, J.N., "An Overview of Theories of Continuum Mechanics with Nonlocal Elastic Response and a General Framework for Conservative and Dissipative Systems." *Applied Mechanics Reviews*. Vol. **69** (2017): pp. 030802-1-18.
- [52] Reinaldo Goncalves, R. and Romanoff, J. "Size-dependent modelling of elastic sandwich beams with prismatic cores." *Solids and Structures*. Vol. **136-137** (2018): pp. 28-37. doi.org/10.1016/j.ijsolstr.2017.12.001

[53] Karttunen, A.T., Reddy, J.N., and Romanoff, J. "Micropolar modeling approach for periodic sandwich beams." *Composite Structures*. Vol. 185 (2018): pp. 656-664. doi.org/10.1016/j.compstruct.2017.11.064

[54] Fleck, N.A. and Hutchinson, J.W., "A phenomenological theory for strain gradient effects in plasticity." *Journal of Mechanics and Physics of Solids*. Vol. **41** (1993), pp. 1825-1857.

[55] Fleck, N.A., Muller, G.M., Ashby, M.F. and Hutchinson, J.W. "Strain-gradient plasticity: theory and experiment", *Acta Metallurgica*. Vol. **42** (1994): pp. 475-487.

[56] Peerlings, R.H.J., Geers, M.G.D., de Borst, R. and Brekelmans, W.A.M. "A critical comparison of non-local and gradient-enhanced softening continua." *Solids and Structures*. Vol. **38** (2001): pp. 7723-7746.

[57] Bazant, Z.P. and Jirasek, M. "Nonlocal integral formulations of plasticity and damage: survey of progress." *Journal of Engineering Mechanics*. **November** (2002): pp. 1119-1149.

List of Figures

Fig. 1. Top left. Example of periodic beam and its kinematics with periodic and homogenized solutions. Bottom left. Reasons for variation of T-joint rotation stiffness. Right. Comparison of accuracy of deflection and stress prediction with classical and couple stress -based Timoshenko beam theory. Reproduced from Refs. [19,20].

Fig. 2. Multilevel analysis approach for the fatigue strength and response assessment of thin-walled structures a) from joint through panel to hull girder level, b) modeling non-linear joints in global model using Equivalent Single Layer theory and c) the difference between nominal stress states in panels with symmetric and non-symmetric joints (all panels with equal cross-sectional area). Taken from Ref. [23].

Fig. 3. Influence of distorted thin decks to load-carrying mechanism of a prismatic passenger ship. Taken from Ref. [23].

Fig. 4. Modeling fracture in ship deck with openings using A) ESL B) 3D-FEA and C) local fracture criterion. D) comparison between ESL and 3D for deck with and without rectangular cutout. Produced from Ref. [29].

Fig. 5. Modeling buckling in ship deck with openings using 3D shell element and Equivalent Single Layer Modeling. Reproduced from Ref. [35].

Fig. 6. Fully coupled geometrically non-linear analysis between primary, secondary and tertiary scales. Reproduced from Ref. [34].

Fig. 7. Failure locations for full-scale panels and corresponding FEA. Reproduced from [22].

Fig. 8. Stress state assessment at the laser-hybrid welds and complexity of the stress state based on geometry and the loading mode. Reproduced from Refs. [22,42].

Figure Caption List

Fig. 1. Top left. Example of periodic beam and its kinematics with periodic and homogenized solutions. Bottom left. Reasons for variation of T-joint rotation stiffness. Right. Comparison of accuracy of deflection and stress prediction with classical and couple stress -based Timoshenko beam theory. Reproduced from Refs. [19,20].

Fig. 2. Multilevel analysis approach for the fatigue strength and response assessment of thin-walled structures a) from joint through panel to hull girder level, b) modeling non-linear joints in global model using Equivalent Single Layer theory and c) the difference between nominal stress states in panels with symmetric and non-symmetric joints (all panels with equal cross-sectional area). Taken from Ref. [23].

Fig. 3. Influence of distorted thin decks to load-carrying mechanism of a prismatic passenger ship. Taken from Ref. [23].

Fig. 4. Modeling fracture in ship deck with openings using A) ESL B) 3D-FEA and C) local fracture criterion. D) comparison between ESL and 3D for deck with and without rectangular cutout. Produced from Ref. [29].

Fig. 5. Modeling buckling in ship deck with openings using 3D shell element and Equivalent Single Layer Modeling. Reproduced from Ref. [35].

Fig. 6. Fully coupled geometrically non-linear analysis between primary, secondary and tertiary scales. Reproduced from Ref. [34].

Full-field geometry and distortion measurements of a structure

Modification of idea structure to consider manufacturing induced distortions

Geometrically non-linear analysis of initially distorted structure

Fig. 7. Failure locations for full-scale panels and corresponding FEA. Reproduced from [22].

Fig. 8. Stress state assessment at the laser-hybrid welds and complexity of the stress state based on geometry and the loading mode. Reproduced from Refs. [22,42].